

FEMALE END VIEW

1 = ORANGE
2 = ORANGE
3 = GREEN/YELLOW
4 = ORANGE
5 = WHITE/ORANGE

LOCKNUT

Ø28.6 [1.13] REF.
1/2" THREAD

SPECIFICATIONS

CONTACT CARRIER MATERIAL	NYLON OR TPU
CONTACT MATERIAL/PLATING	BRASS/GOLD
HOUSING MATERIAL/PLATING	BRASS/NICKEL
O-RING MATERIAL	NITRILE
RATED CURRENT [A]	2.0 A
RATED VOLTAGE [V]	60 VAC/75 VDC
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS [AWG]	5x18 AWG
TEMPERATURE RANGE	-40°C to +105°C (-40°F to +221°F)
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP68

24.0 [0.94] HEX STOCK
Ø25.0 [0.98]

KEYWAY ORIENTATION MAY VARY FROM WHAT IS SHOWN

29.2 [1.15]
11.5 [0.45]
12.7 [0.50]
50.0mm (±10mm)
1/2-14NPT
7.0 [0.28]
Ø14.1 [0.56]
M12x1
LOCKNUT
O-RING

* METERS
SEE NOTE 1

WRAP LABELS
(SEE NOTE 3)

CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm

* UNLESS OTHERWISE SPECIFIED

NOTES:

1. "*" INDICATES LEAD LENGTHS IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

2. "/CS16485" DESIGNATES NEXT GEN3 JUNE 2020 UPDATE. CODE D - EURO 5 PIN - CUSTOM WIRING USING 18 AWG CONDUCTORS. FRONT MOUNT RECEPTACLES TO INCLUDE LOCK NUT AND O-RING.

3. WRAP LABELS ON ALL CONDUCTORS. WRAP LABELS NUMBERED WITH CORRESPONDING WIRE IDENTIFICATION NUMBERS. ("1" EQUALS "ORANGE #1")

RELATED DOCUMENTS

1.
2.
3.
4.

MATERIAL

SEE SPECIFICATIONS

FINISH

SEE SPECIFICATIONS

3RD ANGLE PROJECTION

THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.

DRFT RDS
APVD A.K.

UNIT OF MEASUREMENT
MILLIMETER [INCH]

DO NOT SCALE THIS DRAWING

TURCK

3000 CAMPUS DRIVE
MINNEAPOLIS, MN 55441
1-800-544-7769
(763) 553-7300
(763) 553-0708 fax
www.turck.us

DATE 03/22/18
SCALE 1=1.0

DESCRIPTION
FK 4.5-*/14.5/NPT/CS16485

IDENTIFICATION NO.
REV C

FILE: 777041269
SHEET 1 OF 1