




12345678

1 = WHITE/ORANGE (+TX) 2 = ORANGE (-TX) 3 = WHITE/GREEN (+RX) 4 = N/C 5 = N/C 6 = GREEN (-RX) 7 = N/C 8 = N/C

SPECIFICATIONS				
CONTACT CARRIER MATERIAL/COLOR	POLYCARBONATE/CLEAR			
MOLDED HEAD MATERIAL/COLOR	TPU/TEAL			
CONTACT MATERIAL/PLATING	BRONZE/GOLD			
RATED CURRENT [A]	1.5 A			
RATED VOLTAGE [V]	42 V			
OUTER CABLE JACKET MATERIAL/COLOR	TPE/TEAL			
CONDUCTOR INSULATION MATERIAL	HDPE			
NUMBER OF CONDUCTORS [AWG]	2UTPx24 AWG, STRANDED, CAT 5e			
TEMPERATURE RANGE	-40°C to +80°C (-40°F to +176°F)			
PROTECTION CLASS (RJ45)	IP20			



CABLE LENGTH	TOLERANCE *			
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER			
STRIP LENGTH	TOLERANCE *			
0-7mm	±0.5mm			
8-29mm	±1.0mm			
30-49mm	±2.0mm			
50-69mm	±3.0mm			
70-100mm	±4.0mm			
OVER 100mm	±5.0mm			
* UNLESS OTHERWISE SPECIFIED				

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

A	DRAWING RELEASE	RDS	10/07/19	
REV	DESCRIPTION	BY	DATE	ECO NO.

CABLE PROPERTIES: OIL, UV, WELD SLAG, AND ABRASION RESISTANT				
VOLTAGE RATINGS (MAX): 600V				
CATEGORY:	CAT 5e; (CABLE WILL MEET CAT 5e CHANNEL REQUIREMENTS TO 85M LENGTH)			
POE COMPLIANT (802.3af):	UP TO 85M LENGTH WHEN INSTALLED PER RECOMMENDATIONS IN TIA TSB-184			
FLEXLIFE:	10X CABLE OD MIN: 1 MILLION CYCLES (TICK TOCK)			
	20X CABLE OD MIN: 10 MILLION CYCLES (TICK TOCK)			

"440" RAW CABLE SPECIFICATIONS

TORSION TEST: 3 MILLION CYCLES (11b LOAD, 360'-71 CYCLES/min)

C(UL)US CMX-OUTDOOR-CM LISTED, AWM RECOGNIZED COMPLIANT WITH NEC ARTICLE 800 COMMUNICATIONS CABLES

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		IRCK "	000 CAMPUS DRIVE NEAPOLIS, MN 55441 -800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us
MATERIAL		DRFT RDS	DATE 07/09/18	DESCRIPTION RJ45C RJ45C 4	4∩_*M
ALL DIMENSIONS DISPLAYED ON THIS		APVD L.S.	SCALE 1=1.0	10430 10430 4	40- W
	DRAWING ARE FOR REFERENCE ONLY		IEASUREMENT IDENTIFICATION NO		I pp./
FINISH	INCIPERENCE ONE			IDENTIFICATION NO.	REV
	CONTACT TURCK FOR MORE INFORMATION	MILLIMETE	ER [INCH]		А
		DO NOT SCALE	THIS DRAWING	FILE: 777041346	SHEET 1 OF 1

APPROVALS: