


FEMALE END VIEW



A = RED (VCC)
 B = BROWN (TX-, OUTPUT SIGNAL)
 C = GREEN (TX+, OUTPUT SIGNAL)
 D = BLUE (RX-, INPUT SIGNAL)
 E = WHITE (RX+, INPUT SIGNAL)
 F = BLACK (GROUND)

CONNECTOR


TYPE/STYLE - MS 3116M

SHELL SIZE - 10

INSERT ARRANGEMENT - 6S

SPECIFICATIONS

CONTACT CARRIER MATERIAL	NEOPRENE
MOLDED HEAD MATERIAL/COLOR	PVC/BLACK
CONTACT MATERIAL/PLATING	COPPER ALLOY/GOLD
COUPLING NUT MATERIAL/PLATING	ALUMINUM ALLOY/OLIVE DRAB CHROMATE
MOLD SLEEVE	ALUMINUM/BLACK ANODIZED
RATED CURRENT [A]	4.4 A
RATED VOLTAGE [V]	300 V
OUTER JACKET MATERIAL/COLOR	TPU/BLACK
CONDUCTOR INSULATION MATERIAL	HDPE
NUMBER OF CONDUCTORS	2STPx24 AWG + 2x24 AWG
SHIELDING	ALUMINUM FOIL SHIELD, 24 AWG DRAIN
TEMPERATURE RATING	-40°C to +80°C (-40°F to +176°F)
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP67,IP68
CONNECTOR TYPE	MIL-DTL-26482




CABLE LENGTH	TOLERANCE *
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE *
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
* UNLESS OTHERWISE SPECIFIED	

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTH.

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		TURCK 3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us				
								
MATERIAL	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	DRFT	NF	DATE	05/01/18	DESCRIPTION MS 3116M-10-6S-2582-*		
SEE SPECIFICATIONS		APVD	R.P.	SCALE	1=1.5			
FINISH		CONTACT TURCK FOR MORE INFORMATION	UNIT OF MEASUREMENT			IDENTIFICATION NO.		REV A
SEE SPECIFICATIONS			MILLIMETER [INCH]					
			DO NOT SCALE THIS DRAWING			FILE: 777041553		SHEET 1 OF 1

A	DRAWING RELEASE	NF	05/31/18	
REV	DESCRIPTION	BY	DATE	ECO. NO.