

FEMALE END VIEW

1 = BLUE

2 = BLUE

3 = BLUE

4 = BLUE

5 = BLUE

6 = BLUE

7 = BLUE

8 = BLUE

9 = BLUE

10 = WHITE/BLUE

11 = BLUE

12 = BLUE

13 = BLUE

14 = WHITE/BLUE

15 = BLUE

16 = BLUE

M23 connector

PANEL CUTOUT (TYP.)

$\varnothing 25.0 + 0.1$

$[\varnothing 0.98 + .004]$

BASIC THRU

11.6 [0.46]

9.3 [0.37] REF.

NON-ROTATIONAL THRU

SPECIFICATIONS

CONTACT CARRIER MATERIAL/COLOR	NYLON or PBT/WHITE
CONTACT MATERIAL/PLATING	BRASS/GOLD
CONNECTOR HOUSING MATERIAL/PLATING	BRASS/NICKEL
O-RING/GASKET MATERIAL	RUBBER (NITRILE or FPM)
RATED CURRENT [A]	3.0 A
RATED VOLTAGE [V]	150 V
NUMBER OF CONDUCTORS [AWG]	16x18 AWG
PROTECTION CLASS	IEC IP65

END VIEW
LOCKNUT NOT SHOWN FOR CLARITY

O-RING GROOVE

28.8 [1.13]

10.0 [0.39]

50.0mm ±10mm

25x1.5

LOCKNUT

O-RING

WRAP LABELS (SEE NOTE 4)

NOTES:

1. "*" INDICATES LEAD LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.
2. MAXIMUM WALL THICKNESS 6.5 [0.256].
3. "/S613" DESIGNATES 18 AWG CONDUCTORS.
4. "/CS16527" DESIGNATES NEXT GEN3 JUNE 2020 UPDATE. CODE A – M23 16 PIN – CUSTOM WIRING. REAR MOUNT RECEPTACLES TO INCLUDE LOCK NUT AND O-RING INSTALLED ON BODY.
5. WRAP LABELS ON ALL CONDUCTORS. WRAP LABELS NUMBERED WITH CORRESPONDING WIRE IDENTIFICATION NUMBERS. ("1" EQUALS "BLUE #1")

CABLE LENGTH	TOLERANCE *
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE *
0–7mm	±0.5mm
8–29mm	±1.0mm
30–49mm	±2.0mm
50–69mm	±3.0mm
70–100mm	±4.0mm
OVER 100mm	±5.0mm
* UNLESS OTHERWISE SPECIFIED	

SOURCE DRAWING – FOR REFERENCE ONLY

RELATED DOCUMENTS

1.

2.

3.

4.

MATERIAL

SEE SPECIFICATIONS

FINISH

SEE SPECIFICATIONS

3RD ANGLE PROJECTION

ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY

CONTACT TURCK FOR MORE INFORMATION

THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.

DRFT NF

APVD D.L.

DATE 05/22/18

SCALE 1=1.0

UNIT OF MEASUREMENT

MILLIMETER [INCH]

DO NOT SCALE THIS DRAWING

3000 CAMPUS DRIVE
MINNEAPOLIS, MN 55441
1-800-544-7769
(763) 553-7300
(763) 553-0708 fax
www.turck.us

DESCRIPTION

CKFD 16-16-*/S613/CS16527

IDENTIFICATION NO.

REV

C

FILE: 777041577

SHEET 1 OF 1

C	UPDATE CONDUCTOR COLORS AND NOTES	RDS	07/20/20	500000001668
REV	DESCRIPTION	BY	DATE	ECO NO.