


FEMALE END VIEW




A = VIOLET
B = RED
C = GRAY
D = RED/BLU
E = GREEN
F = BLUE
G = GRN/PNK
H = WHITE
I = YELLOW
J = PINK
K = GRN/YEL
L = BROWN
M = BRN/GRN
N = BLACK

CONNECTOR
TYPE/STYLE - MS 3108M
SHELL SIZE - 20
INSERT ARRANGEMENT - 27S

SPECIFICATIONS


CONTACT CARRIER MATERIAL	NEOPRENE
MOLDED HEAD MATERIAL/COLOR	PVC/BLACK
CONTACT MATERIAL/PLATING	COPPER ALLOY/SILVER
COUPLING NUT MATERIAL/PLATING	ALUMINUM ALLOY/OLIVE DRAB CHROMATE
MOLD SLEEVE	ALUMINUM/BLACK ANODIZED
RATED CURRENT [A]	5.5 A
RATED VOLTAGE [V]	500 V
OUTER JACKET MATERIAL/COLOR	PVC/YELLOW
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS	14x18 AWG
TEMPERATURE RATING	-40°C to +105°C (-40°F to +221°F)
PROTECTION CLASS	MEETS IEC IP67
CONNECTOR TYPE	MIL-DTL-5015



SOURCE DRAWING - FOR REFERENCE ONLY

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTH.

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION			THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.				3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us	
MATERIAL SEE SPECIFICATIONS	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	DRFT	ER	DATE	06/13/19	DESCRIPTION MS 3108M-20-27S-1097-*			
FINISH SEE SPECIFICATIONS		APVD	J.B.	SCALE	1=2.0				
		UNIT OF MEASUREMENT MILLIMETER [INCH]				IDENTIFICATION NO.		REV	
		DO NOT SCALE THIS DRAWING				FILE: 777042175		SHEET 1 OF	

B	UPDATE MOLD BODY	NF	05/25/23	78609
REV	DESCRIPTION	BY	DATE	ECO. NO.