


MALE END VIEW




A = BROWN
B = TAN
C = BLUE
D = YELLOW/BROWN
E = GREEN
F = WHITE/YELLOW
G = PINK
H = BROWN/GREEN
J = BLACK
K = WHITE/GREEN
L = RED/BLUE
M = GRAY/PINK
N = ORANGE
P = GRAY
R = RED
S = WHITE
T = VIOLET
U = GRAY/BROWN
V = YELLOW

CONNECTOR
TYPE/STYLE - MS 3116M
SHELL SIZE - 14
INSERT ARRANGEMENT - 19P

SPECIFICATIONS

CONTACT CARRIER MATERIAL	NEOPRENE
MOLDED HEAD MATERIAL/COLOR	PVC/BLACK
CONTACT MATERIAL/PLATING	COPPER ALLOY/GOLD
COUPLING NUT MATERIAL/PLATING	ALUMINUM ALLOY/OLIVE DRAB CHROMATE
MOLD SLEEVE	ALUMINUM/BLACK ANODIZED
RATED CURRENT [A]	2.0 A
RATED VOLTAGE [V]	300 V
OUTER JACKET MATERIAL/COLOR	TPU/BLACK
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS	19x22 AWG
DRAIN/SHIELD	24 AWG/ALUM.-POLYESTER FOIL
TEMPERATURE RATING	-40°C TO +90°C (-40°F TO +194°F)
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP67, IP68
CONNECTOR TYPE	MIL-DTL-26482



CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
*UNLESS OTHERWISE SPECIFIED	

NOTES:

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTH.

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION 	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		TURCK 3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us	
MATERIAL	SEE SPECIFICATIONS	DRFT	NF	DATE	09/18/18
FINISH	SEE SPECIFICATIONS	APVD	M.V.	SCALE	1=2.0
		UNIT OF MEASUREMENT		DESCRIPTION	
		MILLIMETER [INCH]		MS 3116M-14-19P-0996-*	
		DO NOT SCALE THIS DRAWING		IDENTIFICATION NO.	REV
				FILE: 777042271	B
				SHEET 1 OF 1	

B	UPDATE COUPLING NUT	RDS	11/25/19	75441
REV	DESCRIPTION	BY	DATE	ECO. NO.