


FEMALE END VIEW




1 = BLACK
2 = WHITE
3 = RED
4 = GREEN



SPECIFICATIONS

CONTACT CARRIER MATERIAL	NYLON or TPU
MOLDED HEAD MATERIAL/COLOR	TPU/BLACK
CONTACT MATERIAL/PLATING	BRASS/GOLD
COUPLING NUT MATERIAL/FINISH	STAINLESS STEEL/PASSIVATED
RATED CURRENT [A]	4.0 A
RATED VOLTAGE [V]	250 V
OUTER CABLE JACKET MATERIAL/COLOR	EX60/BLACK
CONDUCTOR INSULATION MATERIAL	XLPE
NUMBER OF CONDUCTORS [AWG]	4x18 AWG (2 PAIRS)
DRAIN/SHIELD	20 AWG/ALUM.-POLYESTER FOIL
CONDUCTOR ARRANGEMENT	2 SHIELDED TWISTED PAIRS, 1 DRAIN
TEMPERATURE RANGE	-40°C to +90°C (-40°F to +194°F)
PROTECTION CLASS	MEETS IEC IP67




CABLE LENGTH	TOLERANCE *
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE *
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
* UNLESS OTHERWISE SPECIFIED	

NOTES:

- "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.
- "/S618" DESIGNATES ALUMINIZED POLYESTER SHIELD AND DRAIN WIRE. DRAIN WIRE NOT CONNECTED AT MOLDED END.
- "/S1353" DESIGNATES EXTREMLIFE-60 RATED CABLE. PRODUCTS SHOULD USE FLAG LABELS IN PLACE OF WRAP LABELS.
- "/S3369" DESIGNATES BLACK CABLE AND BLACK PLUG BODY.
- TRIM UNUSED DRAIN AND SHIELD BACK TO CABLE JACKET ON BOTH ENDS.

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION			THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.			3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us	
MATERIAL	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	DRFT	ER	DATE	01/15/19	DESCRIPTION WKCV 4.4T-* /S618/S1353/S3369		
SEE SPECIFICATIONS		APVD	M.V.	SCALE	1=1.0			
FINISH		UNIT OF MEASUREMENT MILLIMETER [INCH]				IDENTIFICATION NO.		REV A
SEE SPECIFICATIONS								
		FILE: 777042721				SHEET 1 OF 1		

A	DRAWING RELEASE	ER	01/23/19	
REV	DESCRIPTION	BY	DATE	ECO. NO.