



FEMALE END VIEW		MALE END VIEW		SPECIFICATIONS																													
																																	
A = BROWN B = TAN C = BLUE D = YELLOW/BROWN E = GREEN F = WHITE/YELLOW G = PINK H = BROWN/GREEN J = BLACK K = WHITE/GREEN L = RED/BLUE M = GRAY/PINK N = ORANGE P = GRAY R = RED S = WHITE T = VIOLET U = GRAY/BROWN V = YELLOW		A = BROWN B = TAN C = BLUE D = YELLOW/BROWN E = GREEN F = WHITE/YELLOW G = PINK H = BROWN/GREEN J = BLACK K = WHITE/GREEN L = RED/BLUE M = GRAY/PINK N = ORANGE P = GRAY R = RED S = WHITE T = VIOLET U = GRAY/BROWN V = YELLOW																															
CONNECTOR TYPE/STYLE - MS 3116M SHELL SIZE - 14 INSERT ARRANGEMENT - 19S		CONNECTOR TYPE/STYLE - MS 3116M SHELL SIZE - 14 INSERT ARRANGEMENT - 19P																															
				<table><tr><td>CONTACT CARRIER MATERIAL</td><td>NEOPRENE</td></tr><tr><td>MOLDED HEAD MATERIAL/COLOR</td><td>PVC/BLACK</td></tr><tr><td>CONTACT MATERIAL/PLATING</td><td>COPPER ALLOY/GOLD</td></tr><tr><td>COUPLING NUT MATERIAL/PLATING</td><td>ALUMINUM ALLOY/OLIVE DRAB CHROMATE</td></tr><tr><td>MOLD SLEEVE</td><td>ALUMINUM/BLACK ANODIZED</td></tr><tr><td>RATED CURRENT [A]</td><td>2.0 A</td></tr><tr><td>RATED VOLTAGE [V]</td><td>300 V</td></tr><tr><td>OUTER JACKET MATERIAL/COLOR</td><td>TPU/BLACK</td></tr><tr><td>CONDUCTOR INSULATION MATERIAL</td><td>PVC</td></tr><tr><td>NUMBER OF CONDUCTORS</td><td>19x22 AWG</td></tr><tr><td>DRAIN/SHIELD</td><td>24 AWG/ALUM.-POLYESTER FOIL</td></tr><tr><td>TEMPERATURE RATING</td><td>-40°C TO +90°C (-40°F TO +194°F)</td></tr><tr><td>PROTECTION CLASS</td><td>MEETS NEMA 1,3,4,6P AND IEC IP67, IP68</td></tr><tr><td>CONNECTOR TYPE</td><td>MIL-DTL-26482</td></tr></table>		CONTACT CARRIER MATERIAL	NEOPRENE	MOLDED HEAD MATERIAL/COLOR	PVC/BLACK	CONTACT MATERIAL/PLATING	COPPER ALLOY/GOLD	COUPLING NUT MATERIAL/PLATING	ALUMINUM ALLOY/OLIVE DRAB CHROMATE	MOLD SLEEVE	ALUMINUM/BLACK ANODIZED	RATED CURRENT [A]	2.0 A	RATED VOLTAGE [V]	300 V	OUTER JACKET MATERIAL/COLOR	TPU/BLACK	CONDUCTOR INSULATION MATERIAL	PVC	NUMBER OF CONDUCTORS	19x22 AWG	DRAIN/SHIELD	24 AWG/ALUM.-POLYESTER FOIL	TEMPERATURE RATING	-40°C TO +90°C (-40°F TO +194°F)	PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP67, IP68	CONNECTOR TYPE	MIL-DTL-26482
CONTACT CARRIER MATERIAL	NEOPRENE																																
MOLDED HEAD MATERIAL/COLOR	PVC/BLACK																																
CONTACT MATERIAL/PLATING	COPPER ALLOY/GOLD																																
COUPLING NUT MATERIAL/PLATING	ALUMINUM ALLOY/OLIVE DRAB CHROMATE																																
MOLD SLEEVE	ALUMINUM/BLACK ANODIZED																																
RATED CURRENT [A]	2.0 A																																
RATED VOLTAGE [V]	300 V																																
OUTER JACKET MATERIAL/COLOR	TPU/BLACK																																
CONDUCTOR INSULATION MATERIAL	PVC																																
NUMBER OF CONDUCTORS	19x22 AWG																																
DRAIN/SHIELD	24 AWG/ALUM.-POLYESTER FOIL																																
TEMPERATURE RATING	-40°C TO +90°C (-40°F TO +194°F)																																
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP67, IP68																																
CONNECTOR TYPE	MIL-DTL-26482																																

<table><tr><th>CABLE LENGTH</th><th>TOLERANCE*</th></tr><tr><td>ALL LENGTHS</td><td>+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER</td></tr><tr><th>STRIP LENGTH</th><th>TOLERANCE*</th></tr><tr><td>0-7mm</td><td>±0.5mm</td></tr><tr><td>8-29mm</td><td>±1.0mm</td></tr><tr><td>30-49mm</td><td>±2.0mm</td></tr><tr><td>50-69mm</td><td>±3.0mm</td></tr><tr><td>70-100mm</td><td>±4.0mm</td></tr><tr><td>OVER 100mm</td><td>±5.0mm</td></tr><tr><td colspan="2">* UNLESS OTHERWISE SPECIFIED</td></tr></table>		CABLE LENGTH	TOLERANCE*	ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER	STRIP LENGTH	TOLERANCE*	0-7mm	±0.5mm	8-29mm	±1.0mm	30-49mm	±2.0mm	50-69mm	±3.0mm	70-100mm	±4.0mm	OVER 100mm	±5.0mm	* UNLESS OTHERWISE SPECIFIED																																																																					
CABLE LENGTH	TOLERANCE*																																																																																								
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER																																																																																								
STRIP LENGTH	TOLERANCE*																																																																																								
0-7mm	±0.5mm																																																																																								
8-29mm	±1.0mm																																																																																								
30-49mm	±2.0mm																																																																																								
50-69mm	±3.0mm																																																																																								
70-100mm	±4.0mm																																																																																								
OVER 100mm	±5.0mm																																																																																								
* UNLESS OTHERWISE SPECIFIED																																																																																									
NOTES: 1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTH.																																																																																									
SOURCE DRAWING - FOR REFERENCE ONLY <table><tr><td colspan="2">RELATED DOCUMENTS</td><td colspan="2">3RD ANGLE PROJECTION</td><td colspan="2">THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.</td><td colspan="2">3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us</td></tr><tr><td colspan="2">1. 2. 3. 4.</td><td colspan="2"></td><td colspan="2"></td><td colspan="2">TURCK</td></tr><tr><td colspan="2">MATERIAL</td><td colspan="2">ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY</td><td colspan="2">DRFT NF</td><td colspan="2">DATE 02/03/20</td></tr><tr><td colspan="2">SEE SPECIFICATIONS</td><td colspan="2"></td><td colspan="2">APVD M.V.</td><td colspan="2">SCALE 1=2.0</td></tr><tr><td colspan="2">FINISH</td><td colspan="2">CONTACT TURCK FOR MORE INFORMATION</td><td colspan="2">UNIT OF MEASUREMENT</td><td colspan="2">DESCRIPTION</td></tr><tr><td colspan="2">SEE SPECIFICATIONS</td><td colspan="2"></td><td colspan="2">MILLIMETER [INCH]</td><td colspan="2">MS 3116M-14-19S-0996-* -14-19P</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2">DO NOT SCALE THIS DRAWING</td><td colspan="2">IDENTIFICATION NO.</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">REV</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">A</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">FILE: 777044037</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">SHEET 1 OF 1</td></tr></table>		RELATED DOCUMENTS		3RD ANGLE PROJECTION		THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us		1. 2. 3. 4.						TURCK		MATERIAL		ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY		DRFT NF		DATE 02/03/20		SEE SPECIFICATIONS				APVD M.V.		SCALE 1=2.0		FINISH		CONTACT TURCK FOR MORE INFORMATION		UNIT OF MEASUREMENT		DESCRIPTION		SEE SPECIFICATIONS				MILLIMETER [INCH]		MS 3116M-14-19S-0996-* -14-19P						DO NOT SCALE THIS DRAWING		IDENTIFICATION NO.								REV								A								FILE: 777044037								SHEET 1 OF 1	
RELATED DOCUMENTS		3RD ANGLE PROJECTION		THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us																																																																																			
1. 2. 3. 4.						TURCK																																																																																			
MATERIAL		ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY		DRFT NF		DATE 02/03/20																																																																																			
SEE SPECIFICATIONS				APVD M.V.		SCALE 1=2.0																																																																																			
FINISH		CONTACT TURCK FOR MORE INFORMATION		UNIT OF MEASUREMENT		DESCRIPTION																																																																																			
SEE SPECIFICATIONS				MILLIMETER [INCH]		MS 3116M-14-19S-0996-* -14-19P																																																																																			
				DO NOT SCALE THIS DRAWING		IDENTIFICATION NO.																																																																																			
						REV																																																																																			
						A																																																																																			
						FILE: 777044037																																																																																			
						SHEET 1 OF 1																																																																																			
<table><tr><td>A</td><td>DRAWING RELEASE</td><td>NF</td><td>02/19/20</td><td></td></tr><tr><td>REV</td><td>DESCRIPTION</td><td>BY</td><td>DATE</td><td>ECO NO.</td></tr></table>		A	DRAWING RELEASE	NF	02/19/20		REV	DESCRIPTION	BY	DATE	ECO NO.																																																																														
A	DRAWING RELEASE	NF	02/19/20																																																																																						
REV	DESCRIPTION	BY	DATE	ECO NO.																																																																																					