

FEMALE END VIEW

TERMINAL BLOCK PLUGS

SPECIFICATIONS	
HOUSING MATERIAL/COLOR	NYLON 66 – 33% GLASS FILLED/BLACK
RECEPTACLE HOUSING MAT'L/FINISH	STAINLESS STEEL/PASSIVATED
CONTACT CARRIER/COLOR	TPU/YELLOW
CONTACT MATERIAL/PLATING	BRASS/GOLD
OPERATING VOLTAGE [V]	300 V
OPERATING CURRENT [A]	4.0 A
PROTECTION CLASS to DIN 40050	IP 67 – ONLY WHEN ALL RECEPTACLES ARE COVERED WITH PLUGS OR CONNECTED
OPERATING TEMPERATURE	–30°C to +80°C (–22°F to +176°F)

WIRING DIAGRAM

J1

WIRING DIAGRAM

J2

COVER SCREWS INCLUDED

FORM 8 CONDUIT BODIES:
10–24 SCREWS

MARK 9 CONDUIT BODIES:
8–32 SCREWS

TERMINAL PLUG
(2 INCLUDED)

RELATED DOCUMENTS	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us	
1.		DRFT	NF	DATE	09/13/18
2.		APVD	T.V.	SCALE	1=1.5
3.	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	UNIT OF MEASUREMENT		DESCRIPTION	
4.		MILLIMETER [INCH]		CA-2/RKFV 80	
MATERIAL	CONTACT TURCK FOR MORE INFORMATION	IDENTIFICATION NO.		REV	
SEE SPECIFICATIONS		U0946-42		A	
FINISH	SEE SPECIFICATIONS	FILE: U0946-42		SHEET 1 OF 1	