




FEMALE END VIEW

PANEL CUTOUT (TYPICAL)



BASIC THRU






NON-ROTATIONAL THRU

M23 connector

SPECIFICATIONS

CONTACT CARRIER MATERIAL/COLOR	NYLON PBT/WHITE
CONTACT MATERIAL/PLATING	BRASS/GOLD
CONNECTOR HOUSING MATERIAL/PLATING	BRASS/NICKEL
SEALING RING	BUNA N OR FLUOR RUBBER
RATED CURRENT [A]	6.0 A MAX.
RATED VOLTAGE [V]	150 V
CONDUCTORS	12 PRINTED CIRCUIT PINS
TEMPERATURE RATING	-40° to +125°C (-40°F to +257°)
PROTECTION CLASS	IEC IP67
MAX. PANEL THICKNESS	6.5mm [.256]


 END VIEW
 LOCKNUT NOT SHOWN
 FOR CLARITY


SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS		3RD ANGLE PROJECTION		THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		TURCK		3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us			
1.		DRFT	RDS	DATE	08/15/06	DESCRIPTION	CKFD 12-PCB				
2.		APVD	JB	SCALE	1=1.0						
3.		ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY		UNIT OF MEASUREMENT		IDENTIFICATION NO.	U2-07596				
4.		SEE SPECIFICATIONS		CONTACT TURCK FOR MORE INFORMATION		REV	A				
FINISH		SEE SPECIFICATIONS		MILLIMETER [INCH]		DO NOT SCALE THIS DRAWING		FILE: U2-07596			
A	DRAWING RELEASE	RDS	09/10/10						SHEET 1 OF 1		
REV	DESCRIPTION	BY	DATE	ECO NO.							