




SPECIFICATIONS				
CONTACT MATERIAL/PLATING	BRASS/GOLD			
CONTACT CARRIER MATERIAL/COLOR	PLASTIC, TPU/BLACK			
CABLE GRIP MATERIAL/COLOR	PLASTIC, PA/BLACK			
COUPLING NUT MATERIAL	ANODIZED ALUMINUM			
SEAL MATERIAL	PLASTIC, NBR			
SCREW-IN THREAD SEAL MATERIAL	PLASTIC, NBR			
DEGREE OF PROTECTION	IP67			
CABLE GRIP RANGE	Ø6−8mm			
SCREW-IN THREAD	PG 9			
RATED VOLTAGE [V]	250 V MAX.			
INSULATION RESISTANCE	≥ 10 Ω ⁹			
RATED CURRENT [A]	9.0 A			
FORWARD RESISTANCE	$\leq 5~\text{m}\Omega$			
TEMPERATURE RATING	-40°C to +90°C (-40°F to +194°F)			







UPDATE LABEL VIEW TO SHOW LABEL ORIENTATION TO KEYRAYS 04/08/13

DESCRIPTION

NOTES:

41583

ECO NO.

DATE

1. "/C1265" DESIGNATES ADDING PART NUMBERS:

10163216 PINCH RING, PG9, 8.5MM 10163225 PRESSING SCREW, PG9, 8.5MM

TO BOM AND RE-PACKAGE.

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		`www.tur	MN 55441 4-7769 -7300 -0708 fax
MATERIAL		DRFT RDS	DATE 05/16/08	DESCRIPTION BK 4140-0/9/C1265/FF	
SEE SPECIFICATIONS SEE SPECIFICATIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY		APVD	SCALE 1=1.0	BK 4140-0/9/C1203/FF	
		UNIT OF MEASUREMENT		IDENTIFICATION NO.	
FINISH	CONTACT TURCK	MILLIMETER [INCH]		U2-13609	I B
SEE SPECIFCATIONS	FOR MORE INFORMATION				
	DO NOT SCALE	THIS DRAWING	FILE: U2-13609 SHE	ET 1 OF 1	