

FEMALE END VIEW

1 = BLUE (- VOLTAGE)  
2 = BROWN (+ VOLTAGE)  
3 = BARE (SHIELD)  
4 = GREEN/YELLOW (GROUND)

(SCALE 2:1)

WIRE SIDE VIEW  
OF CONTACT HOLDER  
TO SHOW LABEL DETAILS

LABEL ORIENTATION  
TO KEYWAY

NOTES:

1. "/C1265" DESIGNATES ADDING PART NUMBERS:

10163216 PINCH RING, PG9, 8.5MM  
10163225 PRESSING SCREW, PG9, 8.5MM

TO BOM AND RE-PACKAGE.

RELATED DOCUMENTS

1.  
2.  
3.  
4.

MATERIAL

SEE SPECIFICATIONS

FINISH

SEE SPECIFICATIONS

3RD ANGLE  
PROJECTION

ALL DIMENSIONS  
DISPLAYED ON THIS  
DRAWING ARE FOR  
REFERENCE ONLY

CONTACT TURCK  
FOR MORE  
INFORMATION

THIS DRAWING IS  
CONFIDENTIAL AND THE  
PROPERTY OF TURCK  
INC. USE OF THIS  
DOCUMENT WITHOUT  
WRITTEN PERMISSION IS  
PROHIBITED.

DRFT RDS  
APVD

DATE 05/16/08  
SCALE 1=1.0

UNIT OF MEASUREMENT  
MILLIMETER [ INCH ]

DO NOT SCALE THIS DRAWING

TURCK INC

High Technology Sensors and Automation Controls

3000 CAMPUS DRIVE  
MINNEAPOLIS, MN 55441  
1-800-544-7769  
(763) 553-7300  
(763) 553-0708 fax  
turck.com

DESCRIPTION

BKV 4140-0/9/C1265/FF

IDENTIFICATION NO.

U2-13612

REV

C

FILE: U2-13612

SHEET 1 OF 1

HOUSING MATERIAL/COLOR

GLASS FILLED NYLON/BLACK

CONTACT MATERIAL/PLATING

BRASS/GOLD

COUPLING NUT MATERIAL/FINISH

316 STAINLESS STEEL/PASSIVATED

RATED CURRENT [A]

9.0 A

RATED VOLTAGE [V]

300 V

MAXIMUM WIRE SIZE

16 AWG

TERMINATION METHOD

SCREW TERMINAL

CABLE GRIP RANGE

8.5mm

TEMPERATURE RATING

-40°C to +90°C (-40°F to +194°F)

PROTECTION CLASS

MEETS NEMA 1,3,4,6P AND IEC IP 67

C

UPDATE CABLE GRIP RANGE

NF

01/09/15

48374

REV

DESCRIPTION

BY

DATE

ECO NO.