

FEMALE END VIEW

1 = BLUE (- VOLTAGE)
2 = BROWN (+ VOLTAGE)
3 = BARE (SHIELD)
4 = GREEN/YELLOW (GROUND)

FOUNDATION™
fieldbus

(SCALE 2:1)

BLUE=1
BROWN=2
3=GRAY
4=GREEN

WIRE SIDE VIEW
OF CONTACT HOLDER
TO SHOW LABEL DETAILS

LABEL ORIENTATION
TO KEYWAY

SPECIFICATIONS	
HOUSING MATERIAL/COLOR	GLASS FILLED NYLON/BLACK
CONTACT MATERIAL/PLATING	BRASS/GOLD
COUPLING NUT MATERIAL	STAINLESS STEEL
RATED CURRENT [A]	9.0 A
RATED VOLTAGE [V]	600 V
MAXIMUM WIRE SIZE	16 AWG
TERMINATION METHOD	SCREW TERMINAL
CABLE GRIP RANGE	8–10mm
TEMPERATURE RATING	–40°C to +90°C (–40°F to +194°F)
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP 67

RELATED DOCUMENTS

1.
2.
3.
4.

MATERIAL

SEE SPECIFICATIONS

FINISH

SEE SPECIFICATIONS

3RD ANGLE
PROJECTION

ALL DIMENSIONS
DISPLAYED ON THIS
DRAWING ARE FOR
REFERENCE ONLY

CONTACT TURCK
FOR MORE
INFORMATION

THIS DRAWING IS
CONFIDENTIAL AND THE
PROPERTY OF TURCK
INC. USE OF THIS
DOCUMENT WITHOUT
WRITTEN PERMISSION IS
PROHIBITED.

DRFT RDS
APVD

UNIT OF MEASUREMENT
MILLIMETER [INCH]

DO NOT SCALE THIS DRAWING

DATE 05/04/10
SCALE 1=1.0

DESCRIPTION
BKV 4140-0/11/FF

IDENTIFICATION NO.
U2-17238

REV
C

3000 CAMPUS DRIVE
MINNEAPOLIS, MN 55441
1-800-544-7769
(763) 553-7300
(763) 553-0708 fax
www.turck.us

C	UPDATE LABEL VIEW TO SHOW LABEL ORIENTATION TO KEYWAY	WBS	04/08/13	41853
REV	DESCRIPTION	BY	DATE	ECO. NO.