


FEMALE END VIEW


35.9 [1.41] REF.
ASSEMBLED HEIGHT $\varnothing 19.6$ [0.77]

M12x1

20.0 [0.79]

KEY-WAY
ADJUSTABLE
BY 90°
INCREMENTS54.0 [2.13]
APPROX. $\varnothing 8.0$ [0.32] MAX
CABLE DIAMETER $\varnothing 18.0$ [0.71]

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS		3RD ANGLE PROJECTION		THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED. TURCK		3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us	
1. 2. 3. 4.							
MATERIAL		DRFT RDS		DATE 05/04/10		DESCRIPTION CMBD 8241-0/PG9	
SEE SPECIFICATIONS		APVD		SCALE 1=1.0			
FINISH		UNIT OF MEASUREMENT MILLIMETER [INCH]		IDENTIFICATION NO. U2-17342		REV A	
SEE SPECIFICATIONS							
		CONTACT TURCK FOR MORE INFORMATION		DO NOT SCALE THIS DRAWING		FILE: U2-17342	
						SHEET 1 OF 1	

ALL METAL SHIELDED FIELD WIREABLE CONNECTOR