

MALE END VIEW

FEMALE END VIEW

TYPICAL PANEL CUTOUT

SPECIFICATIONS

CONTACT CARRIER MATERIAL	TPU
CONTACT MATERIAL/PLATING	BRASS/GOLD
HOUSING MATERIAL/FINISH	STAINLESS STEEL/PASSIVATED
RATED CURRENT [A]	15.0 A
RATED VOLTAGE [V]	600 V
TEMPERATURE RATING	-40°C to +105°C (-40°F to +221°F)
PROTECTION CLASS	MEETS NEMA 1,3,4 AND IEC IP67
ACCOMODATES WALL THICKNESS	.040" (1.0 mm) to .875" (22.2 mm)
GASKET MATERIAL	BUNA N

LOCKNUT AND WASHERS
NOT SHOWN FOR
CLARITY

LOCKNUT
LOCK WASHER
SEE NOTE 1
THRUST WASHER
SEALING GASKET

CAUTION:
RISK OF ELECTRICAL SHOCK
DO NOT DISCONNECT UNDER LOAD

SOURCE DRAWING - FOR REFERENCE ONLY

NOTE(S):
1. LOCK WASHER TO BE INSTALLED ON THREADS AS SHOWN.

C	UPDATE CONTACT HOLDERS FROM PVC TO TPU	RDS	12/01/15	52552
REV	DESCRIPTION	BY	DATE	ECO NO.

RELATED DOCUMENTS

1.
2.
3.
4.

MATERIAL

SEE SPECIFICATIONS

FINISH

SEE SPECIFICATIONS

3RD ANGLE PROJECTION

THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.

DRFT RDS
APVD

DATE 09/01/11
SCALE 1=1.0

UNIT OF MEASUREMENT
MILLIMETER [INCH]

CONTACT TURCK FOR MORE INFORMATION

DO NOT SCALE THIS DRAWING

TURCK INC
High Technology Sensors and Automation Controls

3000 CAMPUS DRIVE
MINNEAPOLIS, MN 55441
1-800-544-7769
(763) 553-7300
(763) 553-0708 fax
turck.com

DESCRIPTION

RSFV RKFV 44/22

IDENTIFICATION NO.

U2-19251

REV

C

FILE: U2-19251

SHEET 1 OF 1