


MALE END VIEW


	PIN	T568A	T568B	PROFINET
12345678	1	WHITE/GREEN	WHITE/ORANGE	YELLOW
	2	GREEN	ORANGE	ORANGE
	3	WHITE/ORANGE	WHITE/GREEN	WHITE
	4	BLUE	BLUE	N/C
	5	WHITE/BLUE	WHITE/BLUE	N/C
	6	ORANGE	GREEN	BLUE
	7	WHITE/BROWN	WHITE/BROWN	N/C
	8	BROWN	BROWN	N/C

SPECIFICATIONS					
HOUSING MATERIAL	DIE-CAST ZINC				
MOLDED PART MATERIAL	PA				
CONDUCTOR SIZE RATING [AWG]	22—26 AWG, STRANDED 22—26 AWG, SOLID				
CABLE DIAMETER RANGE	ø5.5mm-8.5mm [0.22"-0.35"]				
SHIELD CONNECTION	360° CONTACT, SPRING LOADED				
NOMINAL CURRENT	1.0 A				
NOMINAL VOLTAGE	50 VDC (MAX.)				
OPERATING TEMPERATURE	-40°C to +70°C (-40°F to +158°F)				
PROTECTION CLASS	IP20				
RF TRANSMISSION PARAMETER	CAT. 6A				
TRANSFER IMPEDENCE/SHIELD ATTENUATION	CAT. 6A				









SOURCE DRAWING - FOR REFERENCE ONLY

	RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.	High Technology	RCK InC Sensors and Automation Controls	3000 CAMPUS MINNEAPOLIS, MN 1-800-544- (763) 553-7 (763) 553-0 turck.com	N 55441 7769 '300 9708 fax
	MATERIAL		DRFT RDS	DATE 10/13/11	CONNECTOR. FW.RJ45		CAT 6
	SEE SPECIFICATIONS	ALL DIMENSIONS DISPLAYED ON THIS	APVD A.A.	SCALE 1=1.0	CONNECTOR, TW, R04	55 80 IDC	CALO
		DRAWING ARE FOR REFERENCE ONLY	UNIT OF ME	ASUREMENT			051
	FINISH	HEILINGE ONE			IDENTIFICATION NO.		REV
093		CONTACT TURCK		ER[INCH]	U2-19	271	В
	SEE SPECIFICATIONS	INFORMATION					
) NO.). DO NO			THIS DRAWING	FILE: U2-19271	SHEET	1 OF 1

NOTES:

- 1. ALL DIMENSIONS REFERENCE.
- 2. ASSEMBLY INSTRUCTIONS INCLUDED IN THE BAG.

 B
 UPDATE DESCRIPTION AND CATEGORY
 RDS
 11/03/11
 37093
 SEE
 SPECIFICATIONS
 MILL

 REV
 DESCRIPTION
 BY
 DATE
 ECO NO.
 DO NO.