	MALE END VIEW (P1)	FEMALE END VIEW		SPECI	FICATIONS	
			-			
$\frac{1}{2} \underbrace{1}{1} \underbrace{1}{1} \underbrace{1}{2} \underbrace{1}{1} \underbrace{1}$		(31-34)				
	$5 + \frac{15}{7} = 7$ $3 = PORT 1-4$	3				
				· · · · · · · · · · · · · · · · · · ·		
		2 4		· · · · · · · · · · · · · · · · · · ·	,	
$\frac{1}{2} + \frac{1}{2} + \frac{1}$	14 + 600 + 16 7 = PORT 2-3			, , ,		
Connector 0 0.00000000000000000000000000000000000						
2 10 <td< td=""><td></td><td>1 5</td><td></td><td></td><td></td></td<>		1 5				
	2 10 11 = PORT 3-3	6				
$\underbrace{\begin{array}{c} 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 $				PROTECTION CLASS to DIN 40050		
 M.3.3 connector M.3.3 connector M.3.3 connector M.3.4 connector M.3.5 connector M.3				OPERATING TEMPERATURE	-40°C to +80°C (-40°F to +176°F)	
W 23 connector 19 : 2004/01 10 : 2004/01 <						
$\frac{1}{2} = CORRUNT T = CORR$	18 = PORT 4-5					
Image: Control of the control of th	19 = COMMON					
$\frac{1}{2 \times \left[(2 \times 8 \right] \times 10^{-4} \right] + (1 \times 0 \times 10^{-5} \right]}{(2 \times 10^{-4} \times 1$	10-32 ENCLOSURE					
$\frac{1}{2 \times 1 \times 10^{49} \text{ Hz}}, \frac{1}{6 \times 10^{10} \text{ Hz}}, \frac{1}{6 \times 10^$						
				1 >	< 1	
12.4 [0.49] REF. Image: Ref.<				2 >		
$\frac{1}{2} + \frac{1}{2} + \frac{1}$	12.4 [0.49] REF.	☐ _ 6.0 [0.24 ⁻		J1 3>		
$\frac{1}{2 \text{ LORARIZE FOR TATURE RATING RATE RATING REF VALUE 20 NO INTO SCREWS (2 NOT INCLUDED).}{2 \text{ LORARIZE NOT RESCREWS (2 NOT INCLUDED).}}$				5 >		
$\frac{1}{2 \text{ LORARIZE FOR TATURE RATING RATE RATING REF VALUE 20 NO INTO SCREWS (2 NOT INCLUDED).}{2 \text{ LORARIZE NOT RESCREWS (2 NOT INCLUDED).}}$						
0 0						
0 0						
Image: Construct and the construct						
B6.0 [3.33] Image: Construction of the provide state of the construction of the provide state of the construction of the constrult of the construction of the constrult of the const	98.0 [3.86]					
Image: construction of the provided in theprovided in the provided in the provided in the provi	86.0 [3.39]		UN 13 10 3 1 12 7 9 16 18 6			
Image: Section 1 (4-20 MOUNTING SCREWS (2 NOT INCLUDED). 7/8-16 UN Image: Section 1 (4-20 MOUNTING SCREWS (2 NOT INCLUDED). Image: Comparison of the production of the pr						
Image: Notes: 1. Clearance Hole For 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). Image: Notes:						
WIRING DIAGRAM WIRING						
WIND DROWN 66.6 [#0.26] THRU 20.3 [0.80] REF. 46.6 [#0.26] THRU 0.10 [3.58] REF. 41.5 [1.36] 0.10 [3.58] REF. 41.5 [1.36] 0.10 [3.58] REF. 1. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). 0.10 [3.58] REF. 1. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). 0.10 [3.58] REF. 1. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). 0.10 [3.58] REF. 1. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). 0.10 [3.58] REF. 1. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). 0.10 [3.58] REF. 1. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). 0.10 [3.58] REF. 1. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). 0.10 [3.58] REF. 1. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). 0.10 [3.58] REF. 1. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). 0.10 [3.58] REF. 1. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). 0.10 [3.58] REF. 1. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). 0.10 [3.58] REF. 1. CLEARANCE HOLE FOR 1/4-20 [3.58] REF. 0.10 [3.58] REF. 1. CLEARANCE HOLE FOR 1/4-20 [3.58] REF. 0.10 [3.58] REF. 1. CLEARANCE						
OUTES: 1. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). REF. Jul DMENSIONS SEE SPECIFICATIONS Mathematical Screws Mathmatical Screws		1_900_544_7760			WIRING DIAGRAM	
96.6 [20,26] THRU 20.3 [0.80] REF. 91.0 [3.58] REF. 91.0 [3.58] REF. 34.5 [1.36] 91.0 [3.58] REF. KEYWAY CAN BE AT ANY POSITON SRD ANGLE NOTES: 1. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). C UPDATE TEMPERATURE RATING NOTES: ALL DIMENSIONS REFERENCE ONLY 1. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). ALL DIMENSIONS FINISH						
00.6. [90.26] [10.2] FRF.						
SEE NOTE 1	Ø6.6 [Ø0.26] THRU_/	20.3 [0.80]				
91.0 [3.58] REF. 44.5 [1.36] 45.5 [1.36] 1.36] 1.36] 1. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). C UPDATE TEMPERATURE RATING NOTES: 2. Support Turck For Marker Source Transport 0.326/19 68987	SEE NOTE 1					
91.0 [3.58] REF. 44.5 [1.36] 45.5 [1.36] 1.36] 1.36] 1. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). C UPDATE TEMPERATURE RATING NOTES: 2. Support Turck For Marker Source Transport 0.326/19 68987						
ALS [1.36] Image: Construct of the second seco						
34.5 [1.36] Image: constrained by the projection of the projectic projection of the projectic projection of th		—91.0 [3.58] REF.————————————————————————————————————				
34.5 [1.36] Image: constrained by the projection of the projectic projection of the projectic projection of th						
NOTES: 1.					SOURCE DRAWING - FOR REFERENCE ONLY	
NOTES: 1.						
1. 1. <td< td=""><td>34.5 [1.36]</td><td></td><td></td><td></td><td></td></td<>	34.5 [1.36]					
3. 3. 4. With the previous of the second seco				PROPERTY OF TURCK		
KEYWAY CAN BE AT ANY POSITON 4. PROHIBITED. www.turck.us NOTES: MATERIAL MATERIAL APVD N.M. SCALE 1=2.0 1. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). FINISH SEE SPECIFICATIONS DATE MACE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). FINISH CONTACT TURCK INFORMATION UNIT OF MEASUREMENT IDENTIFICATION NO. REV C UPDATE TEMPERATURE RATING NF 03/26/19 68987 SEE SPECIFICATIONS SEE SPECIFICATIONS MILLIMETER [INCH] U2-21580 C		/		TOCUMENT WITHOUT		
NOTES: NOTES All DIMENSIONS DISPLAYED ON THIS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY DATE 08/05/11 DESCRIPTION P-4 P-4 RKFV 661-CSV19 1. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). FINISH SEE SPECIFICATIONS All DIMENSIONS DRAWING ARE FOR REFERENCE ONLY N.M. SCALE 1=2.0 P-4 RKFV 661-CSV19 C UPDATE TEMPERATURE RATING NF 03/26/19 68987 SEE SPECIFICATIONS ONTACT TURCK INFORMATION MILLIMETER [INCH] U2-21580 C	KEYWAY CAN BE AT ANY POSITON-/			PROHIBITED.	www.turck.us	
NOTES: SEE SPECIFICATIONS ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY APVD N.M. SCALE 1=2.0 1. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). FINISH FINISH UNIT OF MEASUREMENT IDENTIFICATION NO. REV C UPDATE TEMPERATURE RATING NF 03/26/19 68987 SEE SPECIFICATIONS SEE SPECIFICATIONS MILLIMETER [INCH] U2-21580 C		MATERIAL	DRFT RDS DATE 08/	05/11 DESCRIPTION		
1. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (2 NOT INCLUDED). SEE SPECIFICATIONS UNIT OF MEASUREMENT UNIT OF MEASUREMENT C UPDATE TEMPERATURE RATING NF 03/26/19 68987 SEE SPECIFICATIONS NF 03/26/19 68987	NOTES:		ALL DIMENSIONS APVD N.M. SCALE 1.			
C UPDATE TEMPERATURE RATING NF 03/26/19 68987 SEE SPECIFICATIONS MILLIMETER [INCH] U2-21580 C		SEE SPECIFICATIONS	DRAWING ARE FOR			
C UPDATE TEMPERATURE RATING NF 03/26/19 68987 SEE SPECIFICATIONS FOR MORE INFORMATION	I. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCR	FINISH	REFERENCE ONET	IDENTIFICATION NO. REV		
C UPDATE TEMPERATURE RATING NF 03/26/19 68987 SEE SPECIFICATIONS INFORMATION			_	CONTACT TURCK MILLIMETER INCH	U2-21580 ()	
REV DESCRIPTION BY DATE ECO NO. DO NOT SCALE THIS DRAWING FILE: U2-21580 SHEET 1 OF 1			SEE SPECIFICATIONS	INFORMATION		
	KEV DESCRIPTION	BY DATE ECO NO.		DO NOT SCALE THIS DRAW	ING FILE: UZ-ZISOU SHEET 1 OF 1	