



MALE END VIEW



 Ethernet


SPECIFICATIONS	
CONTACT MATERIAL/PLATING	BRASS/GOLD
COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL
RATED CURRENT [A]	4.0 A
RATED VOLTAGE [V]	250 V
MAXIMUM WIRE SIZE	22 AWG (SOLID OR STRANDED)
CABLE GRIP RANGE	4.5–8.8mm
TEMPERATURE RATING	–40°C to +85°C (–40°F to +185°F)
PROTECTION CLASS	IEC IP67
WIRE TERMINATION	IDC



SOURCE DRAWING – FOR REFERENCE ONLY

ALL METAL SHIELDED FIELD WIREABLE CONNECTOR

C	UPDATE SPECS	NF	02/26/18	64273
REV	DESCRIPTION	BY	DATE	ECO NO.

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION 	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.	3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us		
	MATERIAL SEE SPECIFICATIONS		DRFT KMY APVD E.S.	DATE 06/20/13 SCALE 1=1.0	DESCRIPTION CMBSD 8146-0
	FINISH SEE SPECIFICATIONS		UNIT OF MEASUREMENT MILLIMETER [INCH]		
	CONTACT TURCK FOR MORE INFORMATION		DO NOT SCALE THIS DRAWING		

IDENTIFICATION NO. U2-21772		REV C
FILE: U2-21772		SHEET 1 OF 1