FEMALE END VIEW		SPECIFICATIONS						
			HOUSING MATERIAL/COLOR			NYLON or PBT/BLACK		
					BRASS/GOLD			
			COUPLING NU	IT MATERIAL/PLATING	DIECAST ZINC/NIC	DIECAST ZINC/NICKEL		
(GND) 3 1		RATED CURRENT [A]			9.0 A			
		RATED VOLTAGE [V]			600 V			
		MAXIMUM WIRE SIZE			16 AWG			
4 2		TERMINATION METHOD CABLE GRIP RANGE TEMPERATURE RATING			SCREW TERMINAL PG9 = $6-8mm$ -25°C to +85°C (-13°F to +185°F)			
<u> </u>								
iast.		PROTECTION (IP67				
	KEY-WAY ADJUSTABLE BY 45 INCREMENTS INCREMENTS WIRE SIDE VIEW OF CONTACT HOLDER SHOW LABEL DETAILS	50.4 [1.98] REF. Ø28.0 [1.10	<u>L</u>	PG9 PG9 0.32] MAX CABLE DIAMETER	SOURCE DRAWING - F	OR REFERENCE O	ONLY	
2-	RELATED DOCUMENTS 1.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE		3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441			
	2. 3. 4.	$\Diamond \triangleleft$	WRITTEN PERMISSION IS PROHIBITED.	1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us				
(SCALE 2:1)	MATERIAL		DRFT NF DATE 10/	09/17 DESCRIPTION	17 DESCRIPTION			
		ALL DIMENSIONS DISPLAYED ON THIS				I)		
NOTES:	SEE SPECIFICATIONS	DRAWING ARE FOR	UNIT OF MEASUREMENT					
1. PINOUT REPRESENTS NUMBERING	FINISH	CONTACT TURCK	MILLIMETER [INCH	IDENTIFICATION NO.	2-30654	REV		
A DRAWING RELEASE	SEE SPECIFICATIONS	FOR MORE INFORMATION						
REV DESCRIPTION BY DATE ECO NO.				DO NOT SCALE THIS DRAW	ING FILE: U2-30654	FILE: U2-30654 SHEET		