MALE END VIEW	SPECIFICATIONS		
		HOUSING MATERIAL/COLOR	NYLON or PBT/BLACK
		CONTACT MATERIAL/PLATING	BRASS/GOLD
1 3		COUPLING NUT MATERIAL/PLATING	DIECAST ZINC/NICKEL
		RATED CURRENT [A]	9.0 A
		RATED VOLTAGE [V]	600 V
		MAXIMUM WIRE SIZE	16 AWG
		TERMINATION METHOD	SCREW TERMINAL
		CABLE GRIP RANGE	PG9 = 6-8mm
		TEMPERATURE RATING	-25°C to +85°C (-13°F to +185°F)
		PROTECTION CLASS	IP67
KEY-WAY ADJUSTABLE BY 45' INCREMENTS	50.4 [1.98] Ø28.0 [1.10]-		SOURCE DRAWING - FOR REFERENCE ONLY
	RELATED DOCUMENTS	3RD ANGLE THIS DRAWING IS PROJECTION CONFIDENTIAL AND THE	3000 CAMPUS DRIVE
LABEL ORIENTATION TO KEYWAY (SCALE 2:1)	1. 2. 3. 4.		MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us
	MATERIAL	DRFT RDS DATE 10	D/09/17 DESCRIPTION
NOTES:	SEE SPECIFICATIONS	ALL DIMENSIONS APVD	BS 4241-0/9 (DC PINOUT)
1. PINOUT REPRESENTS NUMBERING FOR DC WIRING.		DISPLAYED ON THIS L.S. DRAWING ARE FOR REFERENCE ONLY UNIT OF MEASUREM	ENT IDENTIFICATION NO. REV
	FINISH	CONTACT TURCK MILLIMETER [IN	
A DRAWING RELEASE RDS 10/11/17			U2-30657 A
REV DESCRIPTION BY DATE ECO NO.	SEE SPECIFICATIONS	DO NOT SCALE THIS DE	RAWING FILE: U2-30657 SHEET 1 OF 1