

MALE END VIEW
1yF 1 3 3 100Ω 2 4 (LONG)
PROFIBUS-PA

SPECIFICATIONS						
CONTACT CARRIER MATERIAL/COLOR	TPU/BLACK					
MOLDED HEAD MATERIAL/COLOR	TPU/BLACK					
CONTACT MATERIAL/PLATING	BRASS/GOLD					
COUPLING NUT MATERIAL/FINISH	STAINLESS STEEL/PASSIVATED					
RATED VOLTAGE [V]	50 V 100 Ω (3 W)					
INTERNAL RESISTOR						
INTERNAL CAPACITOR	1μF					
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP67					





SOURCE DRAWING - FOR REFERENCE ONLY

					RELATED DOCUMENTS	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE			MAINTADO	CAMPUS DRIVE
					1. 2. 3. 4.	*	PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED. High Technology Sensors and Automation Controls PROHIBITED.		1-800 (763) (763)	1-800-544-7769 (763) 553-7300 (763) 553-0708 fax turck.com	
					MATERIAL	ALL DIMENSIONS	DRFT CBM	DATE 08/21/00 SCALE 1=1.0	DESCRIPTION	RSV 48 TR	
						DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	UNIT OF MEASUREMENT		IDENTIFICATION NO.		l REV
					FINISH	CONTACT TURCK FOR MORE	MILLIMETE	ER [INCH]		J2372-719	
D	DRAWING PROCESSED AS PART OF ECO 33971	СВМ	04/07/11	33971		INFORMATION					
REV	DESCRIPTION	BY	DATE	ECO NO.			DO NOT SCALE	THIS DRAWING	FILE: U2372-719		SHEET 1 OF 1