
MALE END VIEW
(8 9 1) (7 12 (0 2) (6 11) 3 (5 4)

SPECIFICATIONS							
CONTACT CARRIER MATERIAL	NYLON or PBT						
CONTACT MATERIAL/PLATING	BRASS/GOLD						
CONNECTOR HOUSING MATERIAL/PLATING	BRASS/NICKEL						
GASKET	RUBBER (NBR or FPM)						
RATED CURRENT [A]	8.0 A						
RATED VOLTAGE [V]	300 V						
MAX. CONDUCTOR SIZE (AWG)	18 AWG						
TERMINATION METHOD	SOLDER LUG						
PROTECTION CLASS	IEC IP65						



SOURCE DRAWING - FOR REFERENCE ONLY

					RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		RC	DLIS, MN 0-544-7 553-73	−7300 −0708 fax	
					MATERIAL	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR	APVD	DATE 7/20/95 SCALE 1=.8 EASUREMENT		CSF 12-0		
					FINISH	CONTACT TURCK		ER[INCH]	IDENTIFICATION NO.	U4520		REV A
Α	DRAWING RELEASE	RDS	12/19/02			FOR MORE INFORMATION						/ \
₹EV	DESCRIPTION	BY	DATE	ECO NO.			DO NOT SCALE	THIS DRAWING	FILE: U4520		SHEET	1 OF 1