

MALE END VIEW

DeviceNet™

BOARD LAYOUT

SPECIFICATIONS

CONTACT CARRIER MATERIAL	NYLON OR TPU
CONTACT MATERIAL/PLATING	BRASS/GOLD
HOUSING, LOCKNUT MATERIAL/PLATING	BRASS/NICKEL
O-RING MATERIAL	NITRILE
RATED CURRENT [A]	4.0 A
RATED VOLTAGE [V]	250 V
TEMPERATURE RATING	-40°C to +90°C (-40°F to +194°F)
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP67
MAX. PANEL THICKNESS	3.0 [0.12]

ORIENTATION OF RIGHT ANGLE CONNECTOR

END VIEW
LOCK NUT AND WASHER
NOT SHOWN

MOUNTING HOLE

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.	3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us	
1.		DRFT DWF	DATE 03/08/99	DESCRIPTION FSFD 57-PCB/S
2.			SCALE 1=0.8	
3.	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	APVD DWF	UNIT OF MEASUREMENT MILLIMETER [INCH]	IDENTIFICATION NO. U5118-57
4.				
MATERIAL	DO NOT SCALE THIS DRAWING	REV F		
FINISH		FILE: U5118-57 SHEET 1 OF 1		