

MALE END VIEW

(LONG)

3

4

2

5

1

mini fast

DeviceNet

PC BOARD LAYOUT

LOCKNUT PG11

SPECIFICATIONS

CONTACT CARRIER MATERIAL	TPU
CONTACT MATERIAL/PLATING	BRASS/GOLD
HOUSING MATERIAL/PLATING	BRASS/NICKEL
RATED CURRENT [A]	9.0 A
RATED VOLTAGE [V]	160 VAC
NUMBER OF CONDUCTORS	5 PRINTED CIRCUIT PINS
TEMPERATURE RATING	-40°C to +90°C (-40°F to +194°F)
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP67

TYPICAL PANEL CUTOUT

NOTES:

1. PG11 LOCKNUT IS INCLUDED WITH RECEPTACLE.

RELATED DOCUMENTS

1.
2.
3.
4.

MATERIAL

FINISH

3RD ANGLE PROJECTION

THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.

DRFT CBM

APVD

UNIT OF MEASUREMENT

MILLIMETERS

DO NOT SCALE THIS DRAWING

DATE 07/14/99

SCALE 1=1.0

DESCRIPTION

RSF 57-PCB

IDENTIFICATION NO.

U5220-00

REV

F

3000 CAMPUS DRIVE
MINNEAPOLIS, MN 55441
1-800-544-7769
(763) 553-7300
(763) 553-0708 fax
www.turck.us

F	ADD PANEL CUTOUT REFERENCE	KMY	12/03/13	43992
REV	DESCRIPTION	BY	DATE	ECO. NO.