


| SPECIFICATIONS | | | | | | | | | |
|-------------------------------|---|--|--|--|--|--|--|--|--|
| CONTACT CARRIER MATERIAL | NYLON or TPU | | | | | | | | |
| MOLDED HEAD MATERIAL/COLOR | TPU/BLACK | | | | | | | | |
| CONTACT MATERIAL/PLATING | BRASS/GOLD | | | | | | | | |
| COUPLING NUT MATERIAL/PLATING | BRASS/NICKEL | | | | | | | | |
| RATED VOLTAGE [V] | 50 V (7.6 VDC MAX. ON PINS WITH RESISTOR) | | | | | | | | |
| INTERNAL RESISTOR | 220 Ω,1/4 W AND 390 Ω,1/4 W | | | | | | | | |
| PROTECTION CLASS | MEETS IEC IP67 | | | | | | | | |
| TEMPERATURE RATING | -40°C to +80°C (-40°F to +176°F) | | | | | | | | |



SOURCE DRAWING - FOR REFERENCE ONLY

| $\overline{}$ | DESCRIPTION | BY | DATE | ECO NO. | | INFORMATION | DO NOT SCALE | THIS DRAWING | FILE: U8746 | Is | SHEET 1 OF 1 |
|---------------|--|----|------|------------------------|-----------------------|-------------------------------------|---|-----------------|-----------------------------------|----------------|---------------------------|
| - 1 | JPDATE RESISTORS USED RDS 09/16/14 47279 | | - | CONTACT TURCK FOR MORE | MILLIMETER [INCH] | | U8746 E | | | | |
| | | | | | FINISH | REFERENCE ONLY | | | IDENTIFICATION NO. | | |
| | | | | | | DRAWING ARE FOR | | | - | | |
| | | | | | | ALL DIMENSIONS DISPLAYED ON THIS | APVD GC | SCALE 1=.8 | RKSW 45-TR | | |
| | | | | | MATERIAL | | DRFT GC | DATE 05/24/02 | ATE 05/24/02 DESCRIPTION | | |
| | | | | | 2. 3. 4. | $\oplus \Box$ | INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED. | High Technology | / Sensors and Automation Controls | (763) 553_7300 | |
| | | | | | RELATED DOCUMENTS 1. | 3RD ANGLE PROJECTION | THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK | | ick inc | MAINTAROUR | IPUS DRIVE S, MN 55441 |
| | | | | | DELATED DOCUMENTO | 700 111015 | T | T | | | |