


# Compact PROFIsafe / PROFINET Block I/O Module

## Safe Digital Inputs and Outputs

### TBPN-L5-4FDI-4FDX



ID	100001826
<b>Supply</b>	
Supply voltage	24 VDC
Admissible range	20.4...28.8 VDC
Voltage supply connection	5-pin male 7/8" connector X1
Electrical isolation	galvanic isolation of the voltage groups V1 and V2, voltages up to 500 VAC
Power dissipation, typical	≤ 5 W
<b>System data</b>	
Fieldbus transmission rate	100 Mbps
Fieldbus connection technology	2 x M12, 4-pin, D-coded
Web server	integrated
Service interface	Ethernet via P1 or P2

<b>PROFINET</b>	
Addressing	DCP
Conformance class	B (RT)
MinCycleTime	1 ms
Diagnostics	acc. to PROFINET alarm handling
Topology detection	supported
Automatic addressing	supported
Media Redundancy Protocol (MRP)	supported

<b>Safety Data</b>	
PL acc. to EN ISO 13849-1	Level e
Category acc. to DIN EN 13849-1:2008	4
SIL acc. to IEC 61508	3
Useful Lifetime	20 years (EN ISO 13849-1)

- PROFINET slave
- Integrated Ethernet switch
- 100 Mbps supported
- 2 x M12, 4-pin, D-coded Ethernet fieldbus connection
- Glass fiber reinforced housing
- Shock and vibration tested
- Fully potted module electronics
- Protection classes IP65, IP67, IP69K
- 5-pin 7/8" male connector for power supply
- ATEX Zone 2/22
- Four secure digital SIL3 inputs
- Four secure configurable digital SIL3 inputs or outputs

Figure 1






Figure 2



Safety Inputs OSSD	
Low-level signal voltage	EN 61131-2 Type 1 ( < 5 V; < 0.5 mA)
High-level signal voltage	EN 61131-2 Type 1 ( > 15 V; > 2 mA)
Max. OSSD supply per channel	2 A per C0 to C7, 1.5 A at 70 °C Please consider derating as shown in figure 1
Max. tolerance test pulse width	1 ms
Interval between 2 test pulses, minimum	20 ms at 1 ms test pulse width 15 ms at 0.5 ms test pulse width
Safety Inputs floating/antivalent	
Max. loop resistance	< 150 Ω
Max. cable length	max. 1 μF at 150 Ω limited by line capacity
Test pulse, typical	0.6 ms
Test pulse, maximum	0.8 ms
Sensor supply	Power supply V AUX1/T1 max. 2 A Please consider derating as shown in figure 1
Interval between 2 test pulses, minimum	900 ms
Additional information	No connection to external potential allowed
Safety Outputs	
Output current in off state	< 5 V
Output current in off state	< 1 mA suitable for inputs according to EN 61131-2 Type 1
Test pulse, typical	0.5 ms
Test pulse, maximum	1.25 ms
Interval between 2 test pulses, typical	500 ms
Interval between 2 test pulses, minimum	250 ms
Actuator power supply	Power supply V AUX1/T1 max. 2 A Please consider derating as shown in figure 1
Max. output current	2 A (resistive) 1 A (inductive)
Additional information	The load must be mechanically or electrically inert to tolerate the test pulses. When configured as a PM switching output the negative pole of the load should be wired to the M-terminal of the corresponding output (Pin 2).
Connectivity inputs	
Connectivity inputs	M12, 5-pin
Input delay	2.5 ms
Connectivity outputs	
Connectivity outputs	M12, 5-pin
Standard/Directive conformity	
Directive	2006/42/EC Machine Directive 2014/35/EC Low Voltage Directive 2014/30/EC EMC Directive
Vibration test	Acc. to EN 60068-2-6 Acceleration up to 20 g
Shock test	acc. to EN 60068-2-27
Drop and topple	acc. to EN 60068-2-31/IEC 60068-2-32
Electromagnetic compatibility	Acc. to EN 61131-2
Approvals and certificates	CE, FCC, UV-resistant in accordance with DIN EN ISO 4892-2A (2013)
UL Certificate	cULus LISTED 21 W2, Encl.Type 1 IND.CONT.EQ.
Note on ATEX/IECEx	The Quick Start Guide with information on use in Ex Zones 2 and 22 must be observed.




General Information	
Dimensions (W x L x H)	60.4 x 230.5 x 38.8 mm
Ambient temperature	-40...+70 °C
Storage temperature	-40...+85 °C
Altitude	Max. 5000 m
Protection class	IP65 IP67 IP69K
Housing material	PA6-GF30
Housing color	Black
Male connector material	Nickel-plated brass
Window material	Lexan
Material screw	303 stainless steel
Material label	Polycarbonate
Halogen-free	yes
Mounting	2 mounting holes □ 6.3 mm

The data sheet serves as advance information. For definitive values see the corresponding product manual. In this respect, no liability for completeness and accuracy can be applied to the content of this data sheet.





**Accessories**  
 Ethernet cordset (example):  
 RSSD RSSD 441-2M  
 Ident. no. U-02482

M12 × 1 Ethernet





**Accessories**  
 Actuator and sensor cordset, PVC, red plug bodies (example):  
 RK 4.5T-2-WS 4.5T/S1055  
 Ident. no. 100031634

M12 × 1 Safety Inputs




**Accessories**  
 Actuator and sensor cordset, PVC, red plug bodies (example):  
 RK 4.5T-2-WS 4.5T/S1055  
 Ident. no. 100031634

M12 × 1 Safety I/O Port



**Accessories**  
 Power supply cordset (example):  
 RSM RKM 50-2M  
 Ident. no. U2282-0

7/8" Power Supply



## Module Status LED

LED	Color	Status	Description
ETH1 / ETH2	Green	On	Ethernet Link (100 Mbps)
		flashing	Ethernet communication (100 Mbps)
		Off	No Ethernet link
BUS	Green	On	Active connection to a master
		flashing	Ready
	Red	On	IP-address conflict or Restore Mode or Modbus timeout
flashing		Blink/Wink command active	
	Red/Green	Alternating	Autonegotiation or waiting for DHCP/Boot-P addressing
ERR	Green	On	Diagnostics disabled
	Red	On	Diagnostics enabled
PWR	Green	On	V, power supply OK
		Off	V, power supply off or below defined threshold of 18 V

## LED Status I/O

LED	Color	Status	Description
0...7	Green	On	Channel active
		flashing	Self test
	Red	On	Discrepancy
		flashing	Cross circuit
8...15	Green	On	Channel active
		flashing	Self test (input only)
	Red	On	Discrepancy, overload (output only)
		flashing	Cross circuit

**Process Data Mapping of the Single Protocols**

For more details on the corresponding protocols see manual.