

TX100 HMI Series

10" display with TX VisuPro Runtime

High-Quality Plastic Housing with a Resistive Touch Screen

TX110-00VPST

Type	TX110-00VPST
ID	100002313

Display/touch	
Display	TFT colour
Touchscreen	Resistive, Plastic film front
Active screen area	10.1"
Resolution (pixels)	1024 × 600 pixels WVGA
Format	16:9
Brightness	200 cd/m² typ.
dimmmable	Yes

Controller	
Processor	ARM Cortex A8, 1 GHz
Memory	4 GB Flash
RAM memory	512 MB
Add-on memory	1 x USB host port

Interfaces	
Onboard	1 x RJ45 Ethernet, 1 x RS232/485/422, 1 x USB host, 1 x power supply
Ethernet	1 x 10/100 Mbit
USB	1 × host port
Serial	RS232 / RS485 / RS422

Power supply	
Rated value	24 VDC, max. 0.38 A
Admissible voltage range	10...32 VDC





General data	
Operating ambient conditions	0...50 °C, 5...85 % rel. humidity, non-condensing
Storage ambient conditions	-20...70 °C, 5...85 % rel. humidity, non-condensing
Approvals	CE cULus
Ex approval	Haz. Loc. Class I, Division 2, Groups A, B, C and D
Protection class	IP66 front, IP20 rear NEMA type: 2/4X

Dimensions	
Front (W x H x D)	282 x 197 x 35 mm
Cut-out (W x H)	271 x 186 mm
Mounting depth	29+6 mm
Weight	approx. 1 kg



- 10.1" TFT color display
- LED backlight
- 1024 x 600 pixel resolution
- 64 K colors
- Resistive touch screen
- 1 RJ45 Ethernet port
- 1 serial interface (RS232, RS485, RS422)
- 1 USB host port

Connection and pin assignment

	Power Supply The power supply connector is delivered with each device. 7/8" male receptacle for enclosure (example): RSF 40-1M W/LN Ident. no. U-36648	Pin Assignment  1 = 24 VDC 2 = 0 V 3 = $\frac{1}{2}$
	USB Interfaces	Pin Assignment  1 = 5 VDC 2 = D⁻ 3 = D⁺ 4 = GND
	Ethernet Ports The Ethernet ports are connected to each other via an internal switch. Ethernet cordsets (examples): RJ45-RJ45: RJ45S RJ45S 441-2M Ident. no. U-06842 RJ45-M12 D-code: RSSD RJ45S 441-2M Ident. no. U3-00525 RJ45-M8: PSGS 4M RJ45S 4413-2M Ident. no. U2-24205 RJ45-M12 D-code female receptacle: RJ45S FKSDSD 441-1M Ident. no. U-03569	Pin Assignment  12345678 1 = TX⁺ 2 = TX⁻ 3 = RX⁺ 4 = n.c. 5 = n.c. 6 = RX⁻ 7 = n.c. 8 = n.c.
	Serial Interface The serial interface can be operated either as RS232, RS485 or RS422. The adjacent wiring diagrams show the respective pin assignments. Attention: In the RS485 mode, pins 3 and 4 as well as 7 and 8 must be externally connected!	Pin Assignment in RS232 Operating Mode  1 = GND 2 = n.c. 3 = TX 4 = RX 5 = n.c. 6 = +5 V output 7 = CTS 8 = RTS 9 = n.c. Pin Assignment in RS485 Operating Mode  1 = GND 2 = n.c. 3 = A 4 = A 5 = n.c. 6 = +5 V output 7 = B 8 = B 9 = n.c. Pin Assignment in RS422 Operating Mode  1 = GND 2 = n.c. 3 = TX⁻ 4 = RX⁻ 5 = n.c. 6 = +5 V output 7 = RX⁺ 8 = TX⁺ 9 = n.c.

Accessories

Type code	Ident-No.		Dimension drawing
TX100-MOUNT-10	100003187	TX100 mounting bracket and power connectors for 10" devices	

Function accessories

Type code	Ident-No.		Dimension drawing
TX-PSC	100002938	Power Supply Male Connector for TX HMI Devices	