


TB-M12-H1147/C53

HF Read/Write Head – For Bus Line Topology with TBEN-*



Technical data

Type	TB-M12-H1147/C53
ID	100003025
Approvals	CE FCC IC MIC UL
Electrical data	
Operating voltage	10...30 VDC
DC rated operational current	≤ 50 mA
inrush current	700 mA For: 1 ms
Data transfer	Inductive coupling
Technology	HF RFID
Operating frequency	13.56 MHz
Radio communication and protocol standards	ISO 15693 NFC Typ 5
Read/Write distance max.	17 mm
Output function	4-wire, Read/Write
Suitable for bus mode to TBEN-*	Yes
Mechanical data	
Mounting conditions	Flush
Ambient temperature	-25...+70 °C
Design	Threaded barrel, M12 x 1
Dimensions	62 mm
Housing diameter	Ø 12 mm
Housing material	Metal, CuZn, Chrome-plated
Active area material	Plastic, PA12-GF30


Features

- M12 × 1 threaded barrel
- Chrome-plated brass
- Device without end termination
- Device may only be operated in line topology TBEN-S*-2RFID-* or TBEN-L*-4RFID-*
- Max. 32 nodes per line or connection permitted
- Use a corresponding terminating resistor (see accessories)
- Observe the performance of the power supply, especially when turned on, and the maximum current carrying capacity of the cables
- Observe the voltage drop on the line
- The maximum possible length of the spur line is 2 m
- The maximum possible length of the bus is 50 m
- By default, a command can only be processed by one read/write head, making HF bus mode suitable for static applications and slow dynamic applications
- In continuous HF bus mode, a command is executed simultaneously on all read/write heads in a bus topology. The recorded data is stored in the ring buffer of the module
- The read/write head is automatically assigned an address
- For different application requirements, the address and can be parameterized
- Powered and operated only via connection to BL ident interface module
- M12 × 1 connector, connection only via BL ident extension cable


.../S2503 Connectors

Technical data


Vibration resistance	55 Hz (1 mm)
Shock resistance	30 g (11 ms)
Protection class	IP67
Electrical connection	Connector, M12 × 1
MTTF	391 years acc. to SN 29500 (Ed. 99) 20 °C
Power-on indication	LED, Green
Packaging unit	1



Connector .../S2500



Connector .../S2501



Functional principle


The HF read/write devices operating at a frequency of 13.56 MHz form a transmission zone, the size of which (0...500 mm) varies depending on the combination of read/write device and tag used.

The read/write distances mentioned here only represent standard values measured under laboratory conditions, free from any influences caused by surrounding materials.

The read/write distances of the tags for mounting in metal TW-R**-M(MF) were determined in metal.

Attainable distances may vary by up to 30 % due to component tolerances, mounting conditions, ambient conditions and material qualities (especially when mounted in metal). Testing of the application under real operating conditions is therefore essential, especially with on-the-fly reading and writing!









Mounting instructions/Description















Diameter active area B Ø 12 mm

flush mounting

LED	Color	Status	Meaning
1	OFF	OFF	Operating voltage switched off
	GREEN	ON	Operating voltage switched on
	GREEN	FLASHING (1 Hz)	HF field switched off
	GREEN	FLASHING (2 Hz)	Tag in detection range

Dimensions	Type designation	Read-write distance		Transfer zone		Minimum distance between two read-write heads
	Ident - no.	Recommended (mm)	max. [mm]	length max. [mm]	width offset max. [mm]	
	TW-R4-3-M-B320-10PCS 100013771	1	2	4	2	36
	TW-R7.5-B128 7030231	5	10	8	4	36
	TW-R9.5-B128 7030252	5	11	5	2	36
	TW-R9.5-K2 7030558	5	10	10	5	36
	TW-R10-M-B146 7030545	3	6	9	4	36
	TW-R10-M-K2 100002368	3	6	9	4	36
	TW-R12-M-B146 7030500	3	6	9	4	36
	TW-R16-B128 6900501	0	0	0	0	36

	TW-R16-K2 7030410	0	0	0	0	36
	TW-R20-B128 6900502	5	11	16	8	36
	TW-R20-B320 100005244	0	0	0	0	36
	TW-R20-K2 6900505	5	12	16	8	36
	TW-R30-B128 6900503	7	15	22	11	36
	TW-R30-B320 100005245	7	15	22	11	36
	TW-R30-K2 6900506	6	13	20	10	36
	TW-R30-K9 7030565	5	11	20	10	36
	TW-R4-22-B128 7030237	2	4	11	5	36
	TW-L18-18-F-B128 7030634	6	13	6	3	36

	TW-L36-18-F-B320-100PCS 100025059	6	13	32	16	36
	TW-L40-P-B128-100PCS 7030658	6	17	30	15	36
	TW-R15-B320 10004102	6	13	6	3	36