



DW6000-155-8C-H1441

Draw-Wire – Analog

Features

- Measuring range up to 6000mm
- M12 connector
- Protection class: IP65 (Encoder)
- Analog output, 0...10V
- Supply voltage 12...30 VDC

Wiring diagram



Technical data

Type	DW6000-155-8C-H1441
ID	1544550
General data	
Measuring range	6000 mm
Linearity deviation	≤ 0.1 %
Electrical data	
Operating voltage U_B	12...30 VDC
No-load current	≤ 22.5 mA
Short-circuit protection	yes
Wire break/reverse polarity protection	yes
Output function	4-wire, Analog output
Voltage output	0...10 V
Current consumption	22,5 mA
Mechanical data	
Design	Draw Wire
Housing material	Titanium anodized aluminium
min. extension force	8.8 N
max.extension force	12.3 N
max. extension speed	10 m/s
Pull acceleration max.	140 m/s ²
wire material	Stainless steel
Electrical connection	Connector, M12 × 1
Environmental conditions	
Ambient temperature	-20...+60 °C

Technical data

Protection class	IP65
------------------	------

Signal	+U _B	Analog out	Gnd	Analog Gnd	-	-	-	-	-
Pin configuration	1	2	3	4	-	-	-	-	-

Accessories

RDR-1	1544753
-------	---------

Deflection roller for aluminium draw-wire sensors

