


# BI5-G18SK-AN6X2

## Inductive Sensor

### Features


- M18 × 1 threaded barrel
- Chrome-plated brass
- DC 3-wire, 10...30 VDC
- NO contact, NPN output
- Terminal chamber

### Wiring diagram



### Functional principle

Inductive sensors detect metal objects contactless and wear-free. For this, they use a high-frequency electromagnetic AC field that interacts with the target. Inductive sensors generate this field via an RLC circuit with a ferrite coil.



### Technical data

|                                        |                                                     |
|----------------------------------------|-----------------------------------------------------|
| Type                                   | BI5-G18SK-AN6X2                                     |
| ID                                     | 4642500                                             |
| General data                           |                                                     |
| Rated switching distance               | 5 mm                                                |
| Mounting conditions                    | Flush                                               |
| Secured operating distance             | $\leq (0.81 \times S_n)$ mm                         |
| Correction factors                     | St37 = 1; Al = 0.3; stainless steel = 0.7; Ms = 0.4 |
| Repeat accuracy                        | $\leq 2$ % of full scale                            |
| Hysteresis                             | 3...15 %                                            |
| Electrical data                        |                                                     |
| Operating voltage $U_B$                | 10...30 VDC                                         |
| Ripple $U_{ss}$                        | $\leq 10$ % $U_{Bmax}$                              |
| DC rated operating current $I_o$       | $\leq 200$ mA                                       |
| No-load current                        | $\leq 15$ mA                                        |
| Residual current                       | $\leq 0.1$ mA                                       |
| Isolation test voltage                 | 0.5 kV                                              |
| Short-circuit protection               | yes/Cyclic                                          |
| Voltage drop at $I_o$                  | $\leq 1.8$ V                                        |
| Wire break/reverse polarity protection | yes/Complete                                        |
| Output function                        | 3-wire, NO contact, NPN                             |
| Switching frequency                    | 0.5 kHz                                             |
| Mechanical data                        |                                                     |
| Design                                 | Threaded barrel, M18 x 1                            |

## Technical data

|                                       |                                            |
|---------------------------------------|--------------------------------------------|
| Dimensions                            | 77 mm                                      |
| Housing material                      | Metal, CuZn, Chrome-plated                 |
| Terminal chamber cover material       | plastic, Ultem                             |
| Terminal chamber housing material     | plastic, PA12-GF30                         |
| Active area material                  | Plastic, PA12-GF30                         |
| Max. tightening torque of housing nut | 25 Nm                                      |
| Electrical connection                 | Terminal chamber                           |
| Clamping ability                      | ≤ 2.5 mm <sup>2</sup>                      |
| Cable external diameter               | 4.5...8 mm                                 |
| <b>Environmental conditions</b>       |                                            |
| Ambient temperature                   | -25...+70 °C                               |
| Vibration resistance                  | 55 Hz (1 mm)                               |
| Shock resistance                      | 30 g (11 ms)                               |
| Protection class                      | IP67                                       |
| MTTF                                  | 2283 years acc. to SN 29500 (Ed. 99) 40 °C |
| Power-on indication                   | LED, Green                                 |
| Switching state                       | LED, Yellow                                |
| Included in delivery                  | cable gland; 2x plastic seals              |

## Mounting instructions

### Mounting instructions/Description




|                        |         |
|------------------------|---------|
| Distance D             | 2 x B   |
| Distance W             | 3 x Sn  |
| Distance T             | 3 x B   |
| Distance S             | 1.5 x B |
| Distance G             | 6 x Sn  |
| Diameter active area B | Ø 18 mm |

## Accessories

QM-18


6945102



Quick-mount bracket with dead-stop; material: Chrome-plated brass. Male thread M24 × 1.5. Note: The switching distance of the proximity switches may change when using quick-mount brackets.

BST-18B


6947214



Mounting clamp for threaded barrel sensors, with dead-stop; material: PA6

MW18


6945004



Mounting bracket for threaded barrel sensors; material: Stainless steel A2 1.4301 (AISI 304)

BSS-18

6901320



Mounting clamp for smooth and threaded barrel sensors; material: Polypropylene