


SFOL-0.5M

IP-Link Optical Fiber – PUR Cable Jacket



Features

- POF optical fiber for IP-Link
- Fiber core PMMA 980 μm
- Fiber insulation PE 2.2 mm
- PUR jacket, 5.5 mm
- Muting (650 nm) < 190 dB/km
- Muting (660 nm) < 290 dB/km
- Numeric aperture 0.5
- Qualified for drag chain use
- Flame-retardant
- Halogen-free acc. to IEC60754
- Excellent resistance to oil, grease, acids and alkaline solutions
- Cable length: 0.5 m

Functional principle

The photoelectric sensor for IP-Link is a premoulded polymer optical fiber (POF) for the modular fieldbus I/O system piconet.

The possibilities for industrial application range from static installations in cable ducts, pipes and racks up to dynamic installations such as dragchains.

The preassembled IP-Link fiber-optic cable together with the IP-Link socket of the piconet coupling and extension modules are a qualified IP67, shock and vibration tested combination.

Technical data

Type	SFOL-0.5M
ID	6603383
Protection class (When coupled)	When coupled
Connector body	Black
Protection class (When coupled)	Only when screwed together
Cable data	
Cable diameter	Ø 5.5 mm
Length (L)	0.5 m
Cable jacket	PUR, Orange
Electrical properties at +20 °C	
Mechanical and chemical properties	
Bending cycles	≥ 2 million
Other Features	
Qualified for drag chain use	yes
Halogen-free	yes
Oil-resistant	yes