


# PT5000PSIG-2003-I2-H1141



## Pressure Transmitter – With Current Output (2-Wire)



### Features

- Fully welded metal measuring cell
- Pressure range 0...5000 psi rel.
- 7...33 VDC
- Analog output 4...20 mA
- Process connection 1/4"-18 NPT male thread
- Plug-in device, M12 × 1

### Wiring diagram



### Functional principle

The pressure sensors in the PT...-2000 product series operate with a fully welded metal measuring cell in various pressure ranges of up to -1...1000 bar in 2-, 3- or even 4-wire technology. Depending on the sensor variant, the processed signal is available as an analog output signal (4...20 mA, 0...10 V, 0...5 V, 1...6 V, ratiometric) or as a digital IO-Link process parameter. The IO-Link sensor variants also have two independently configurable switching outputs. In addition to the standard variants, there are special sensors for uses such as ATEX areas or for oxygen applications. A wide range of process connections and electrical connections offer a high degree of flexibility in a wide range of applications.

### Technical data

|                                           |                                          |
|-------------------------------------------|------------------------------------------|
| Type                                      | PT5000PSIG-2003-I2-H1141                 |
| ID                                        | 6837352                                  |
| Medium temperature                        | -40...+135 °C                            |
| Pressure type                             | Relative pressure                        |
| Pressure range                            | 0...344.74 bar                           |
|                                           | 0...5000 psi                             |
|                                           | 0...34.47 MPa                            |
| Admissible overpressure                   | ≤ 1200 bar                               |
| Burst pressure                            | ≥ 2400 bar                               |
| Response time                             | < 2 ms, typ. 1 ms                        |
| Long-term stability                       | ± 0.25 % FS, according to IEC EN 60770-1 |
| <b>Power supply</b>                       |                                          |
| Operating voltage U <sub>B</sub>          | 7...33 VDC                               |
| Current consumption                       | ≤ 23 mA                                  |
| Short-circuit/reverse polarity protection | yes / yes                                |
| Insulation class                          | III                                      |
| <b>Outputs</b>                            |                                          |
| Output 1                                  | Analog output                            |
| Output function                           | Analog output current                    |
| <b>Analog output</b>                      |                                          |
| Current output                            | 4...20 mA                                |
| Load                                      | ≤ (supply voltage - 7)/20 kΩ             |
| Resolution                                | <± 0.1 % FS                              |

## Technical data

|                                                 |                                                                                                                  |
|-------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| Accuracy LHR                                    | ±0.3 % FS (typical; max. ±0.5 % FS)                                                                              |
| <b>Mechanical data</b>                          |                                                                                                                  |
| Housing material                                | Stainless-steel/Plastic, 1.4404 (AISI 316L)/polyarylamide 50 % GF UL 94 V-0                                      |
| Process connection                              | 1/4" NPT-18 male thread                                                                                          |
| Pressure connection material                    | Stainless steel 1.4404 (AISI 316L)                                                                               |
| Material pressure transducer                    | Stainless steel 1.4435 (AISI 316L)                                                                               |
| Wrench size pressure connection / coupling nut  | 24                                                                                                               |
| Max. tightening torque of housing nut           | 20 Nm                                                                                                            |
| Electrical connection                           | Connector, M12 × 1                                                                                               |
| Protection class                                | IP67                                                                                                             |
| <b>Environmental conditions</b>                 |                                                                                                                  |
| Ambient temperature                             | -30...+85 °C                                                                                                     |
| Storage temperature                             | -50...+100 °C                                                                                                    |
| Shock resistance                                | 100 g, 11 ms, half sinusoidal curve, all 6 directions, free fall from 1 m onto concrete (6x) acc. to IEC 68-2-27 |
| Vibration resistance                            | 20 g, 15...2000 Hz, 15...25 Hz with amplitude ± 15 mm, 1 octave/minute in all 3 directions, 50 continuous loads  |
| <b>Tests/approvals</b>                          |                                                                                                                  |
| UL registration number                          | E302799                                                                                                          |
| <b>Reference conditions acc. to IEC 61298-1</b> |                                                                                                                  |
| Temperature                                     | 15...+25 °C                                                                                                      |
| Atmospheric pressure                            | 860...1060 hPa abs.                                                                                              |
| Humidity                                        | 45...75 % rel.                                                                                                   |
| Auxiliary power                                 | 24 VDC                                                                                                           |
| <b>Temperature behaviour</b>                    |                                                                                                                  |
| MTTF                                            | 1189 years acc. to SN 29500 (Ed. 99) 40 °C                                                                       |

## Technical data

|                         |                          |
|-------------------------|--------------------------|
| Type                    | PT5000PSIG-2003-I2-H1141 |
| ID                      | 6837352                  |
| Pressure type           | Relative pressure        |
| Pressure range          | 0...344.74 bar           |
|                         | 0...5000 psi             |
|                         | 0...34.47 MPa            |
| Admissible overpressure | ≤ 1200 bar               |

## Technical data

|                                                |                                                                                                                                     |
|------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Burst pressure                                 | ≥ 2400 bar                                                                                                                          |
| Response time                                  | < 2 ms, typ. 1 ms                                                                                                                   |
| Long-term stability                            | 0.25 % FS, according to IEC EN 60770-1                                                                                              |
| <b>Power supply</b>                            |                                                                                                                                     |
| Operating voltage $U_B$                        | 7...33 VDC                                                                                                                          |
| Current consumption                            | ≤ 23 mA                                                                                                                             |
| Short-circuit/reverse polarity protection      | yes / yes                                                                                                                           |
| Protection class                               | IP67                                                                                                                                |
| Insulation class                               | III                                                                                                                                 |
| Insulation voltage                             | 750 VDC                                                                                                                             |
| <b>Outputs</b>                                 |                                                                                                                                     |
| Output 1                                       | Analog output                                                                                                                       |
| Output function                                | Analog output current                                                                                                               |
| <b>Analog output</b>                           |                                                                                                                                     |
| Current output                                 | 4...20 mA                                                                                                                           |
| Load                                           | ≤ (supply voltage - 7)/20 kΩ                                                                                                        |
| Resolution                                     | ≤ ± 0.1 % FS                                                                                                                        |
| Accuracy LHR                                   | ±0.3 % FS (typical; max. ±0.5 % FS)                                                                                                 |
| <b>Temperature behaviour</b>                   |                                                                                                                                     |
| Medium temperature                             | -40...+135 °C                                                                                                                       |
| Temperature coefficient                        | ± 0.2 % of full scale/10 K                                                                                                          |
| <b>Environmental conditions</b>                |                                                                                                                                     |
| Ambient temperature                            | -30...+85 °C                                                                                                                        |
| Storage temperature                            | -50...+100 °C                                                                                                                       |
| Vibration resistance                           | 20 g, 15...2000 Hz, 15...25 Hz with amplitude ± 15 mm, 1 octave/minute in all 3 directions, 50 continuous loads, acc. to IEC 68-2-6 |
| Shock resistance                               | 100 g, 11 ms, half sinusoidal curve, all 6 directions, free fall from 1 m onto concrete (6x) acc. to IEC 68-2-27                    |
| <b>Mechanical data</b>                         |                                                                                                                                     |
| Housing material                               | Stainless-steel/Plastic, 1.4404 (AISI 316L)/polyarylamide 50 % GF UL 94 V-0                                                         |
| Pressure connection material                   | Stainless steel 1.4404 (AISI 316L)                                                                                                  |
| Material pressure transducer                   | Stainless steel 1.4435 (AISI 316L)                                                                                                  |
| Process connection                             | 1/4" NPT-18 male thread                                                                                                             |
| Wrench size pressure connection / coupling nut | 24                                                                                                                                  |
| Electrical connection                          | Connector, M12 × 1                                                                                                                  |

## Technical data

|                                          |                                            |
|------------------------------------------|--------------------------------------------|
| Max. tightening torque of housing nut    | 20 Nm                                      |
| Reference conditions acc. to IEC 61298-1 |                                            |
| Temperature                              | 15...+25 °C                                |
| Atmospheric pressure                     | 860...1060 hPa abs.                        |
| Humidity                                 | 45...75 % rel.                             |
| Auxiliary power                          | 24 VDC                                     |
| Tests/approvals                          |                                            |
| Approvals                                | cULus                                      |
| UL registration number                   | E302799                                    |
| MTTF                                     | 1189 years acc. to SN 29500 (Ed. 99) 40 °C |