


Flow Rate Monitoring

Inline Sensor with Integrated Processor

FTCI-3/4D15A4P-LI-UP8X-H1141



- Compact inline flow sensor
- Calorimetric principle
- Monitoring of flow rate
- Monitoring of the medium temperature
- For water/glycol mix
- Parametrized via button
- Protected by software code
- DC 4-wire, 21.6...26.4 VDC
- NO/NC prog., PNP output
- 4...20 mA analog output
- Analog output provides a current signal proportional to the flow rate for the overall operating range
- Plug-in device, M12 x 1

ID	6870811
Type	FTCI-3/4D15A4P-LI-UP8X-H1141

Mounting	Inline sensor
Application area	Flow rate and temperature monitoring of water; water/glycol mix or Galden fluid HT110/135
Flow operating range	1...12 gpm
Switch-on time	0...50 s
Switch-off time	0...50 s
Temperature gradient	≤ 400 K/min
Media temperature	14...+194 °F
Ambient temperature	32...+140 °F


Electrical data	
Operating voltage U_a	21.6...26.4 VDC
Current consumption	≤ 100 mA
Output function	PNP/Analog output, NO/NC programmable
Rated operational current	0.2 A
Short-circuit protection	yes
Reverse polarity protection	yes
Current output	4...20 mA
Load	200...500 Ω
Protection class	IP65

Mechanical data	
Design	Inline
Housing material	Plastic, PBT
Sensor material	Stainless steel, 1.4571 (AISI 316Ti)
Electrical connection	Connector, M12 x 1
Process Pressure	20 bar
Process connection	3/4" Swagelok

Flow state display	7-segment display, switching status LED (yellow)
--------------------	--

Tests/approvals	
-----------------	--

Wiring Diagram



Functional principle

The FTCTs from TURCK monitor flow rates of liquids passing through the sensor reliably and wear-free. These sensors are designed for flow rate monitoring.

Based on the thermodynamic principle, electrical energy is converted into heat energy. The heat generated in the probe is conducted away by the flowing medium. The dissipated heat quantity is used as a direct measurement of the medium's flow speed. The integrated microprocessor evaluates the data and calculates the flow rate. Based on the applied principle, the media temperature is also indicated to the user.

In addition to the standardized electrical output signals for industrial applications, the TURCK flow meters also indicate the current flow rate on their 3-digit, 7-segment display.