


FCS-N3/4A4-NA-H1141


Flow Monitoring – Immersion Sensor without Integrated Processor



Features

- Sensor for liquid media
- Calorimetric functionality
- Adjustment via signal processor
- Status indicated via LED chain on signal processor
- Connector device, M12 × 1
- 4-wire connection to the processor

Wiring diagram



Technical data

| | |
|---------------------------------------|--------------------------------------|
| ID | 6871304 |
| Type | FCS-N3/4A4-NA-H1141 |
| Mounting | Immersion sensor |
| Water Operating Range | 1...150 cm/s |
| Oil Operating Range | 3...300 cm/s |
| Stand-by time | typ. 8 s (2...15 s) |
| Switch-on time | typ. 2 s (1...15 s) |
| Switch-off time | typ. 2 s (1...15 s) |
| Temperature jump, response time | max. 12 s |
| Temperature gradient | ≤ 250 K/min |
| Medium temperature | -20...+80 °C |
| Electrical data | |
| Protection class | IP67 |
| Mechanical data | |
| Design | Immersion |
| Housing material | Stainless steel, 1.4571 (AISI 316Ti) |
| Sensor material | Stainless steel, 1.4571 (AISI 316Ti) |
| Max. tightening torque of housing nut | 30 Nm |
| Electrical connection | Connector, M12 × 1 |
| Process Pressure | 100 bar |
| Process connection | 3/4" NPT |

Functional principle

Our insertion - flow sensors operate on the principle of thermodynamics. The measuring probe is heated by several °C as against the flow medium. When fluid moves along the probe, the heat generated in the probe is dissipated. The resulting temperature is measured and compared to the medium temperature. The flow status of every medium can be derived from the evaluated temperature difference. Thus TURCK's wear-free flow sensors reliably monitor the flow of gaseous and liquid media.