

BSV4157-0/13.5

DeviceNet Field Wireable – 7/8" Male, Straight

7/8" Male, Straight

Technische Daten

Type	BSV4157-0/13.5
ID	6914535
Connector A	Male, 7/8"-16 UN, Straight
Number of contacts	5
Contacts	Metal, CuZn, Gold-plated
Contact carriers	Plastic, TPU, Black
Connector body	Plastic, PA 66, Black
Coupling nut	Stainless Steel, 316 (1.4404), Passivated
Acceptable cable diameter	10...12 mm
Core cross-section/Clamping ability	0.14...1.5 mm ²
Connection mode	Screw/clamp connection
Mechanical life	> 100 Mating cycles
Pollution degree	3
Protection class (When coupled)	IP67
Fieldbus	DeviceNet
Electrical properties at +20 °C	
Rated voltage	250 V
Current	9 A
Mechanical and chemical properties	
Ambient temperature range (static)	-25...+85 °C
Ambient temperature range (dynamic)	-40...+90 °C
Note	
- We reserve the right to make technical alterations without prior notice.	

Features

- Straight Male 7/8" minifast Field Wireable
- 5 pins
- Screw termination
- Plastic housing
- 5-pin
- PG13.5 screw-in thread
- Cable feedthrough 10.0...12.0 mm

Contact assignment

