

FKFD 8-x Actuator and Sensor Receptacle – Rear Mount



Technical data

Туре	FKFD 8-x
ID	777001888
Connector A	Female, M12 × 1, A-code
Design specification	Acc. to IEC 61076-2-101
Number of contacts	8
Contacts	Brass, CuZn, Gold-plated
Contact carriers	Plastic, TPU, Black
Connector seal	O-ring, Plastic, FKM/FPM
Housing material/finish	Brass, CuZn, Nickel-plated
Tightening torque (range)	0.4 1.8 Nm (note max. torque of mating connector!)
Mounting orientation	Rear mount
Panel seal	O-ring, NBR
Mounting thread	PG9
Locknut	Brass, CuZn, Nickel-plated
Receptacle mounting torque	2.56.8 Nm
Mechanical life	> 100 Mating cycles
Pollution degree	3
Protection class (When coupled)	IP68
	NEMA: 1, 3, 4, 6P
Total number of conductors	8
Conductor material	TC (tinned copper)
Conductor insulation material	PVC
Conductor size	24 AWG [Similar to 0.25 mm ²]



Circuit Diagram

1)	WH	
2)	BN	
3)	GN	
4) 	YE	
5)+	GY	_
6)	РК	
	BU	
8	RD	



Technical data

.	
Conductor colors	WH, BN, GN, YE, GY, PK, BU, RD
Electrical properties at +20 °C	
Rated voltage	$60 \ V_{\text{\tiny AC}}/75 \ V_{\text{\tiny DC}}$
Current	2 A
Mechanical and chemical properties	
Ambient temperature range (static)	-40+105 °C
Approvals	UL 2238 CE UKCA RoHS
Note	
	 We reserve the right to make technical alterations without prior notice.





Mounting hole - Threaded





2|3



Accessories

FK(S)FD-TOOL



A2550

Tool, knockout hole punch, receptaclemounting hole. Accommodates PG9 threads.



DECAL,9-CLRS,RECEPT+BOXES,EURO(QTY1)

100008955

1 decal sticker containing 9 different color sets of 11 decals to color code a sensor, junction block port, cable end, or receptacle. 5ct 4x9mm rectangles, 4ct 8x19mm rectangles, 1ct 27mm ID ring, 1ct 20mm ID ring.

Accessories

LOCKNUT-PG9-BRASS-(10/BAG)

Locknut, PG9, Brass, Nickel-plated, 10 per bag

100016624

