


# RSM RKM 34P-xM/S4000

## Power Cordset – Extension Cable




### Technische Daten

|                                 |                              |
|---------------------------------|------------------------------|
| Type                            | RSM RKM 34P-xM/S4000         |
| ID                              | 777042863                    |
| Connector A                     | Male, 7/8"-16 UN, Straight   |
| Number of contacts              | 3                            |
| Contacts                        | Brass, CuZn, Gold-plated     |
| Contact carriers                | Plastic, PVC, Black          |
| Connector body                  | Plastic, PVC, Black          |
| Coupling nut                    | Brass, CuZn, Nickel-plated   |
| Tightening torque               | 2 Nm                         |
| Mechanical life                 | > 100 Mating cycles          |
| Pollution degree                | 3                            |
| Protection class (When coupled) | IP67, IP68, IP69, IP69K      |
|                                 | NEMA: 1, 3, 4, 6P, 12        |
| Connector B                     | Female, 7/8"-16 UN, Straight |
| Number of contacts              | 3                            |
| Contacts                        | Brass, CuZn, Gold-plated     |
| Contact carriers                | Plastic, PVC, Black          |
| Connector body                  | Plastic, PVC, Black          |
| Coupling nut                    | Brass, CuZn, Nickel-plated   |
| Tightening torque               | 2 Nm                         |
| Mechanical life                 | > 100 Mating cycles          |
| Pollution degree                | 3                            |
| Protection class (When coupled) | IP67, IP68, IP69, IP69K      |
|                                 | NEMA: 1, 3, 4, 6P, 12        |

### Features

- UL US CE UK CA RoHS compliant IP67/IP68 IP69/IP69K DEGREE OF PROTECTION
- 7/8" Male, Straight, 3-pin
- 7/8" Female, straight, 3-pin
- Power Tray/Exposed Run/Direct Burial Cable
- Black TPE jacket, 3X14 AWG
- Sunlight Resistant
- 40 Cold Bend Rating
- Oil Resistant
- Flame Ratings: UL 1685 FT4, UL 1061, CSA FT1, CSA FT4

### Cable cross section




### Contact assignment


Technische Daten

| Cable data                                                                                                                                                                           |                                  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| Cable ID                                                                                                                                                                             | RF51198                          |
| Total number of conductors                                                                                                                                                           | 3                                |
| Cable diameter                                                                                                                                                                       | Ø 9.6 mm                         |
| Cable jacket                                                                                                                                                                         | TPE, Black                       |
| Conductor diameter                                                                                                                                                                   | 0.12 "                           |
| Conductor material                                                                                                                                                                   | BC (bare copper)                 |
| Conductor insulation material                                                                                                                                                        | PVC/Nylon (Nylon overcoat)       |
| Conductor size                                                                                                                                                                       | 3 x 14 AWG [Similar to 2.50 mm²] |
| Number of strands x O.D.                                                                                                                                                             | 41 x 30 AWG                      |
| Conductor colors                                                                                                                                                                     | GNYE, BK, WH                     |
| Electrical properties at +20 °C                                                                                                                                                      |                                  |
| Rated voltage                                                                                                                                                                        | 600 V                            |
| Current                                                                                                                                                                              | 21 A                             |
| Mechanical and chemical properties                                                                                                                                                   |                                  |
| Bending radius (static)                                                                                                                                                              | ≥ 5 x Ø                          |
| Bending radius (dynamic)                                                                                                                                                             | ≥ 10 x Ø                         |
| UL cold bend rating                                                                                                                                                                  | -40 °C                           |
| Ambient temperature range (static)                                                                                                                                                   | -40...+90 °C                     |
| Ambient temperature range (dynamic)                                                                                                                                                  | 5...+90 °C                       |
| Temperature range (installation)                                                                                                                                                     | -10...+90 °C                     |
| Approval                                                                                                                                                                             |                                  |
| Approvals                                                                                                                                                                            | UL 2237<br>CE<br>UKCA<br>RoHS    |
| Note                                                                                                                                                                                 |                                  |
| - CAUTION: RISK OF ELECTRICAL SHOCK. DO NOT DISCONNECT UNDER LOAD.                                                                                                                   |                                  |
| - Flex ratings may be reduced if used in extreme temperatures, exposure to certain chemicals, operating above the rated cycle speed, or operating below the rated cable bend radius. |                                  |
| - We reserve the right to make technical alterations without prior notice.                                                                                                           |                                  |

Connector A



Connector B



Circuit Diagram

