


8MB12Z-5P3-CS19H

Passive Actuator/Sensor Junction Box, 8 Ports – M12 x 1 I/O port with M23 homerun



Technical data


Type	8MB12Z-5P3-CS19H
ID	E8026482
Distributed I/O	Junction box, 8 -port, with integral M23 x 1 connector
Housing	Plastic, PA6-GF30, Black
Display operating voltage	LED, green
Display switching state	LED, yellow
Switching function	PNP
I/O Port	Female, M12 × 1
Number of contacts	4+PE
Contacts	Brass, CuZn, Gold-plated
Contact carriers	Plastic, PA 4.6 GF30, Black
Connector seal	O-ring, Plastic, FKM/FPM
Housing material/finish	Brass, CuZn, Nickel-plated
Tightening torque (range)	0.8 ... 1 Nm
Mechanical life	> 100 Mating cycles
Pollution degree	3
Protection class (When coupled)	IP67
Homerun connector	Male, M23 × 1, Side exit
Number of contacts	19
Contacts	Brass, CuZn, Gold-plated
Contact carriers	Plastic, PBT, Black
Seal	Plastic, NBR

Features


- UL US
- CE
- UK CA
- RoHS compliant
- IP67 DEGREE OF PROTECTION
- Housing material: PA 6 GF30
- Housing color: Black
- Fully encapsulated
- Protection class: IEC: IP67; NEMA: 1, 3, 4, 6P
- CE compliant
- RoHS compliant
- LED (PNP circuitry)
- I/O port: 5-pin

Contact assignment

I/O Connector



Homerun connector



Technical data

Tightening torque	2 Nm
Mechanical life	> 100 Mating cycles
Pollution degree	3
Protection class (When coupled)	IP67
Electrical properties at +20 °C	
Rated voltage	DC
Rated voltage	10...30 VDC
Current	2 A per signal contact, total current 9 A
Mechanical and chemical properties	
Ambient temperature range (static)	-40...+85 °C
Approvals	UL Listed CE UKCA RoHS
Note	
- We reserve the right to make technical alterations without prior notice.	

Circuit Diagram

