


BLU,TPU,4X18,S-DF,AWM
General Purpose Cable – Reelfast™ Bulk Cable

Features



- General Purpose Cable
- TPU jacket,Blue, shielded, 4X18 AWG
- -40 Cold Bend Rating
- Flame Ratings: UL1061, CSA FT1
- UL/CSA AWM 600V



Technische Daten

Type	BLU,TPU,4X18,S-DF,AWM
ID	RF50840
Cable data	
Cable Platform	General Purpose Cable
Total number of conductors	4
Cable diameter	Ø 6.6 mm
Cable jacket	TPU, Blue
Shielding	Aluminum/polyester (IN), 22 AWG TC (Tinned Copper)
Conductor diameter	0.076 "
Conductor material	TC (tinned copper)
Conductor insulation material	PVC
Conductor size	4 x 18 AWG [Similar to 0.75 mm²]
Number of strands x O.D.	19 x 0.0092 "
Conductor colors	BK, RD, GN, WH
Weight	0.156 lbs. /meter
Electrical properties at +20 °C	
Voltage	UL/CSA AWM 600V
Dielectric withstand (min.)	2 KVAC
DC resistance (max)	7.22 Ω/1000ft max.
Mechanical and chemical properties	
Bending radius (static)	≥ 5 x Ø
Bending radius (dynamic)	≥ 15 x Ø
UL cold bend rating	-40 °C

BLU,TPU,4X18,S-DF,AWM| 22-02-2025 01-58 | Technische Änderungen vorbehalten

Technische Daten

Ambient temperature range (static)	-40...+90 °C
Ambient temperature range (dynamic)	-40...+90 °C
Temperature range (installation)	-20...+90 °C
Approval	
UL Approvals	UL 758 AWM 21744
CSA Approvals	CSA AWM I/II A/B CSA FT1
Compliances	RoHS
Note	
	- Flex ratings may be reduced if used in extreme temperatures, exposure to certain chemicals, operating above the rated cycle speed, or operating below the rated cable bend radius.
	- We reserve the right to make technical alterations without prior notice.