


BLK,PVC,4STPDX22,S-DB,ITC
Instrumentation Tray Cable – Reelfast™ Bulk Cable

Features



- Shielded Twisted Pair
- Instrumentation Tray Cable
- Black PVC jacket, shielded, 4STPDX22 AWG
- Sunlight Resistant
- -40 Cold Bend Rating
- Oil Resistant
- Flame Ratings: UL 1685 FT4, UL1061, CSA FT4
- ITC 150V
- PLTC 300V
- UL/CSA AWM 300V
- CMX OUTDOOR 300V
- CMG 300V



Technische Daten

Type	BLK,PVC,4STPDX22,S-DB,ITC
ID	RF51276
Cable data	
Cable Platform	Instrumentation Tray Cable
Total number of conductors	8
Cable diameter	Ø 8.51 mm
Cable jacket	PVC, Black
Shielding	36 AWG, TC (Tinned Copper), 65% coverage, 24 AWG, TC (Tinned Copper)
Conductor material	TC (tinned copper)
Conductor colors	YE/WH, RD/WH, RD, BK, BK/WH, BU/WH, YE, BU
Description of assembly	STPD (Shielded Twisted Pair, Drain)
Number of pairs	4
Conductor diameter	0.048 "
Conductor insulation material	SR-PVC
Assembly drain	24 AWG, TC (Tinned Copper)
Assembly foil	Foil (IN)
Cable conductor cross-section	2x22 AWG [Similar to 0.34 mm²]
Number of strands x O.D.	19x0.0058 "
Weight	0.244 lbs. /meter
Electrical properties at +20 °C	
Voltage	ITC 150V PLTC 300V UL/CSA AWM 300V CMX OUTDOOR 300V

BLK,PVC,4STPDX22,S-DB,ITC| 22-02-2025 01-54 | Technische Änderungen vorbehalten

Technische Daten

	CMG 300V
Dielectric withstand (min.)	2 KVAC
DC resistance (max)	17.5 Ω /1000ft max.
Mechanical and chemical properties	
Bending radius (static)	$\geq 5 \times \varnothing$
Bending radius (dynamic)	$\geq 15 \times \varnothing$
UL cold bend rating	-40 °C
Ambient temperature range (static)	-40...+105 °C
Ambient temperature range (dynamic)	-40...+105 °C
Temperature range (installation)	-20...+105 °C
Approval	
UL Approvals	UL 2250 ITC UL 13 PLTC Sunlight Resistant -40C Cold Bend Oil Res I Oil Res II UL 758 AWM 2517
CSA Approvals	CSA AWM I/II A/B CMX OUTDOOR-CMG CSA FT4
Compliances	RoHS
Note	
	- Flex ratings may be reduced if used in extreme temperatures, exposure to certain chemicals, operating above the rated cycle speed, or operating below the rated cable bend radius.
	- We reserve the right to make technical alterations without prior notice.