


BLK,TPU,3X24,AWM General Purpose Cable – Reelfast™ Bulk Cable



Features



- General Purpose Cable
- TPU jacket, Black, 3X24 AWG
- -40 Cold Bend Rating
- Flame Ratings: UL1090, CSA FT1
- UL/CSA AWM 300V

Technische Daten

Type	BLK,TPU,3X24,AWM
ID	RF51399
Cable data	
Cable Platform	General Purpose Cable
Total number of conductors	3
Cable diameter	$\varnothing 3.2$ mm
Cable jacket	TPU, Black
Conductor diameter	0.038 "
Conductor material	TC (tinned copper)
Conductor insulation material	SR-PVC
Conductor size	3 x 24 AWG [Similar to 0.25 mm ²]
Number of strands x O.D.	19 x 36 AWG
Conductor colors	BN, BU, BK
Weight	0.035 lbs. /meter
Electrical properties at +20 °C	
Voltage	UL/CSA AWM 300V
Dielectric withstand (min.)	2 KVAC
DC resistance (max)	25.67 Ω /1000ft max.
Mechanical and chemical properties	
Bending radius (static)	$\geq 5 \times \varnothing$
Bending radius (dynamic)	$\geq 10 \times \varnothing$
UL cold bend rating	-40 °C
Ambient temperature range (static)	-40...+80 °C

Technische Daten

Ambient temperature range (dynamic)	-40...+80 °C
Temperature range (installation)	-20...+80 °C
Approval	
UL Approvals	UL 758 AWM 20549
CSA Approvals	CSA AWM I A/B CSA FT1
Compliances	RoHS CE
Note	
	- Flex ratings may be reduced if used in extreme temperatures, exposure to certain chemicals, operating above the rated cycle speed, or operating below the rated cable bend radius.
	- We reserve the right to make technical alterations without prior notice.