



# FSFD 4.4-0.3

## Actuator and Sensor Receptacle – Rear Mount




### Features



- M12, Male, Receptacle, 4-pin
- Mounting thread: PG9

### Contact assignment

Connector A



### Circuit Diagram




### Technical data

|                                 |                                                           |
|---------------------------------|-----------------------------------------------------------|
| Type                            | FSFD 4.4-0.3                                              |
| ID                              | U-22915                                                   |
| Connector A                     | Male, M12 x 1, A-code                                     |
| Design specification            | Acc. to IEC 61076-2-101                                   |
| Number of contacts              | 4                                                         |
| Contacts                        | Brass, CuZn, Gold-plated                                  |
| Contact carriers                | Plastic, Nylon or TPU, Black                              |
| Housing material/finish         | Brass, CuZn, Nickel-plated                                |
| Tightening torque (range)       | 0.4 ... 1.8 Nm<br>(note max. torque of mating connector!) |
| Mounting orientation            | Rear mount                                                |
| Panel seal                      | O-ring, Plastic, NBR                                      |
| Mounting thread                 | PG9                                                       |
| Locknut                         | Brass, CuZn, Nickel-plated                                |
| Receptacle mounting torque      | 2.5...6.8 Nm                                              |
| Mechanical life                 | > 100 Mating cycles                                       |
| Pollution degree                | 3                                                         |
| Protection class (When coupled) | IP68                                                      |
|                                 | NEMA: 1, 3, 4, 6P                                         |
| Total number of conductors      | 4                                                         |
| Length (L)                      | 0.3 m                                                     |
| Conductor material              | TC (tinned copper)                                        |
| Conductor insulation material   | PVC                                                       |
| Conductor size                  | 22 AWG [Similar to 0.34 mm²]                              |


## Technical data

|                                                                            |                                                      |
|----------------------------------------------------------------------------|------------------------------------------------------|
| Conductor colors                                                           | BN, WH, BU, BK                                       |
| <b>Electrical properties at +20 °C</b>                                     |                                                      |
| Rated voltage                                                              | 250 V                                                |
| Current                                                                    | 4 A                                                  |
| <b>Mechanical and chemical properties</b>                                  |                                                      |
| Ambient temperature range (static)                                         | -40...+105 °C                                        |
| Approvals                                                                  | UL 2238<br>CSA C22.2 No. 182.3<br>CE<br>UKCA<br>RoHS |
| <b>Note</b>                                                                |                                                      |
| - We reserve the right to make technical alterations without prior notice. |                                                      |


### Mounting hole - Through



### Mounting hole - Threaded



### Rear-mounted



Accessories

FK(S)FD-TOOL


A2550



Tool, knockout hole punch, receptacle-mounting hole. Accommodates PG9 threads.

DECAL,9-CLRS,RECEPT+BOXES,EURO(QTY1)

100008955



1 decal sticker containing 9 different color sets of 11 decals to color code a sensor, junction block port, cable end, or receptacle. 5ct 4x9mm rectangles, 4ct 8x19mm rectangles, 1ct 27mm ID ring, 1ct 20mm ID ring.

Accessories

LOCKNUT-PG9-BRASS-(10/BAG)

100016624



Locknut, PG9, Brass, Nickel-plated, 10 per bag