




Actuator and Sensor Cable, PVC
TPE cable jacket
RKM 56-2M/S3059



Type	RKM 56-2M/S3059
ID	U-35762
Connector A	Female, 7/8"-16 UN, Straight
Number of contacts	5
Contacts	Brass, CuZn, Gold-plated
Contact carriers	Plastic, TPU, Yellow
Connector body	Plastic, TPU, Yellow
Coupling nut	Brass, CuZn, Nickel-plated
Protection class (When coupled)	IP67, IP68, IP69, IP69K
Mechanical life	> 100 Mating cycles
Pollution degree	3
Cable diameter	Ø 10.01 mm
Length (L)	2 m
Cable jacket	TPE, Yellow
Conductor insulation material	PVC/Nylon (Nylon overcoat)
Conductor colors	WH, RD, GN/YE, OG, BK
Conductor size	5
Number of strands x O.D.	65
Voltage	600 V
Current	10 A

- 7/8" Female, Straight, 5-pin
- Power Tray/Exposed Run/Direct Burial Cable
- Yellow TPE jacket, 5X16 AWG
- Sunlight Resistant
- -40 Cold Bend Rating
- Oil Resistant
- Flame Ratings: UL 1685 FT4, UL 1061, CSA FT1, CSA FT4



Circuit Diagram

1	WH
2	RD
3	GN/YE
4	OG
5	BK