



RSM RKM 36-4M/S3059

Industrial Sensor Cable – TPE cable jacket



Technische Daten

Type	RSM RKM 36-4M/S3059
ID	U-50820
Connector A	Male, 7/8"-16 UN, Straight
Number of contacts	3
Contacts	Brass, CuZn, Gold-plated
Contact carriers	Plastic, TPU, Yellow
Connector body	Plastic, TPU, Yellow
Coupling nut	Brass, CuZn, Nickel-plated
Tightening torque	2 Nm
Mechanical life	> 100 Mating cycles
Pollution degree	3
Protection class (When coupled)	IP67, IP68, IP69, IP69K
	NEMA: 1, 3, 4, 6P, 12
Connector B	Female, 7/8"-16 UN, Straight
Number of contacts	3
Contacts	Brass, CuZn, Gold-plated
Contact carriers	Plastic, TPU, Yellow
Connector body	Plastic, TPU, Yellow
Coupling nut	Brass, CuZn, Nickel-plated
Tightening torque	2 Nm
Mechanical life	> 100 Mating cycles
Pollution degree	3
Protection class (When coupled)	IP67, IP68, IP69, IP69K
	NEMA: 1, 3, 4, 6P, 12


Features

-
-
- 7/8" male, straight, 3-pin
 - 7/8" female, straight, 3-pin
 - Jacket color: yellow
 - Cable length: 4.0 m
 - Protection class: NEMA 1, 3, 4, 6P and IEC IP67
 - 7/8" Male, Straight, 3-pin
 - 7/8" Female, straight, 3-pin
 - Power Tray/Exposed Run/Direct Burial Cable
 - Yellow TPE jacket, 3X16 AWG
 - Sunlight Resistant
 - 40 Cold Bend Rating
 - Oil Resistant
 - Flame Ratings: UL 1685 FT4, UL 1061, CSA FT1, CSA FT4


Cable cross section

Technische Daten

Cable data	
Cable ID	RF51717
Total number of conductors	3
Cable diameter	Ø 8.51 mm
Length (L)	4 m, (+50mm or 4% of length/-0.0, Whichever is greater)
Cable jacket	TPE, Yellow
Conductor diameter	0.105 "
Conductor material	BC (bare copper)
Conductor insulation material	PVC/Nylon (Nylon overcoat)
Conductor size	3 x 16 AWG [Similar to 1.50 mm²]
Number of strands x O.D.	65 x 34 AWG
Conductor colors	GN/YE, BK, WH
Electrical properties at +20 °C	
Rated voltage	600 V
Current	10 A
Mechanical and chemical properties	
Bending radius (static)	≥ 5 x Ø
Bending radius (dynamic)	≥ 10 x Ø
UL cold bend rating	-40 °C
Ambient temperature range (static)	-40...+90 °C
Ambient temperature range (dynamic)	5...+90 °C
Temperature range (installation)	-10...+90 °C
Approval	
Approvals	UL 2238 CSA C22.2 No. 182.3 CE UKCA RoHS
Note	
- Flex ratings may be reduced if used in extreme temperatures, exposure to certain chemicals, operating above the rated cycle speed, or operating below the rated cable bend radius.	
- We reserve the right to make technical alterations without prior notice.	



Contact assignment



Circuit Diagram

