





## Technical data

|                                                                            |                                                      |
|----------------------------------------------------------------------------|------------------------------------------------------|
| Conductor colors                                                           | BN, WH, BU, BK, GY                                   |
| <b>Electrical properties at +20 °C</b>                                     |                                                      |
| Rated voltage                                                              | 250 V                                                |
| Current                                                                    | 4 A                                                  |
| <b>Mechanical and chemical properties</b>                                  |                                                      |
| Ambient temperature range (static)                                         | -40...+105 °C                                        |
| Approvals                                                                  | UL 2238<br>CSA C22.2 No. 182.3<br>CE<br>UKCA<br>RoHS |
| <b>Note</b>                                                                |                                                      |
| - We reserve the right to make technical alterations without prior notice. |                                                      |


### Mounting hole - Through



### Mounting hole - Threaded



### Rear-mounted



Accessories

FK(S)FD-TOOL

A2550




Tool, knockout hole punch, receptacle-mounting hole. Accommodates PG9 threads.

Accessories

LOCKNUT-PG9-BRASS-(10/BAG)


100016624



Locknut, PG9, Brass, Nickel-plated, 10 per bag

DECAL,9-CLRS,RECEPT+BOXES,EURO(QTY1)

100008955



1 decal sticker containing 9 different color sets of 11 decals to color code a sensor, junction block port, cable end, or receptacle. 5ct 4x9mm rectangles, 4ct 8x19mm rectangles, 1ct 27mm ID ring, 1ct 20mm ID ring.