

RKM 40-2M/S90-SP

Power Cordset

Technische Daten

Type	RKM 40-2M/S90-SP
ID	U2-06366
Special version	S90-SP = TPU cable jacket - coil cable
Connector A	Female, 7/8"-16 UN, Straight
Number of contacts	4
Contacts	Brass, CuZn, Gold-plated
Contact carriers	Plastic, TPU, Yellow
Connector body	Plastic, TPU, Yellow
Coupling nut	Brass, CuZn, Nickel-plated
Tightening torque	2 Nm
Mechanical life	> 100 Mating cycles
Pollution degree	3
Protection class (When coupled)	IP67, IP68, IP69, IP69K NEMA: 1, 3, 4, 6P, 12
Length (L)	2 m, (+50mm or 4% of length/-0.0, Whichever is greater)
Electrical properties at +20 °C	
Rated voltage	600 V
Current	9 A
Mechanical and chemical properties	
Approvals	UL 2238 CSA C22.2 No. 182.3 CE RoHS
Note	
- CAUTION: RISK OF ELECTRICAL SHOCK. DO NOT DISCONNECT UNDER LOAD.	
- We reserve the right to make technical alterations without prior notice.	

Features



■ 7/8" Female, Straight, 4-pin

Contact assignment

Connector A

