

WBK 19-0

Actuator and Sensor Field Wireable

Female M23 × 1, Angled

Technische Daten

Type	WBK 19-0
ID	U2-07163
Connector A	Female, M16 × 0.75, Right angle
Number of contacts	19
Contacts	Bronze, CuSn, Gold-plated
Contact carriers	Plastic, PA, Black
Connector body	Plastic, PA, Black
Coupling nut	Brass, CuZn, Nickel-plated
Connector seal	Plastic, NBR
Mounting thread	PG9
Acceptable cable diameter	6...8 mm
Core cross-section/Clamping ability	0.14...24 mm²
Connection mode	Solder contact
Mechanical life	> 500 Mating cycles
Pollution degree	1
Electrical properties at +20 °C	
Rated voltage	30 V
Current	3 A
Insulation resistance	≥ ≥ 10 ⁸ Ω
Mechanical and chemical properties	
Ambient temperature range (static)	-30...+95 °C
Note	
- We reserve the right to make technical alterations without prior notice.	

Features



- Right angle Female M16 versafast Field Wireable
- 19 pins
- Solder termination
- Plastic housing
- Solder connection
- 19-pin
- PG9 screw-in thread
- Cable feedthrough 6.0...8.0 mm

Contact assignment

