


TB-8M8Z-3-FS12

Junction Box - Actuator/Sensor, 8-port – M8 snap, 3 pole I/O port with M12 homerun



Technical data

Type	TB-8M8Z-3-FS12
ID	U2-28811
Distributed I/O	Junction box, 8, with M12 homerun connector
Housing	Plastic, PA 6 GF30, Black
I/O Port	Female, Ø 8 mm
Design specification	Acc. to IEC 61076-2-104
Number of contacts	3
Contacts	Brass, CuZn, Gold-plated
Contact carriers	Plastic, PA 6 GF15, Black
Connector seal	O-ring, Plastic, FKM/FPM
Mechanical life	> 100 Mating cycles
Pollution degree	3
Protection class (When coupled)	IP67
Homerun connector	Male, M12 × 1, Top exit, A-coded
Design specification	Acc. to IEC 61076-2-101
Number of contacts	12
Contacts	Brass, CuZn, Gold-plated
Contact carriers	Plastic, PA 4.6, Black
Tightening torque	0.8 ... 1 Nm (note max. torque of mating connector!)
Mechanical life	> 100 Mating cycles
Pollution degree	3

Features





- Housing material: PA 6 GF30
- Housing color: Black
- Fully encapsulated
- Protection class: IEC: IP67; NEMA: 1, 3, 4, 6P
- CE compliant
- RoHS compliant
- I/O port: 3-pin

Contact assignment

I/O Connector

Homerun connector



Technical data

Protection class (When coupled)	IP67, IP68, IP69, IP69K
	NEMA: 1, 3, 4, 6P
Electrical properties at +20 °C	
Rated voltage	30 VAC/DC
Rated voltage	AC/DC VDC
Current	2 A per contact, total current 2 A4 A total when using additional power connections (pins 11(v-), 12(v+))
Mechanical and chemical properties	
Approvals	CE UKCA RoHS
Note	
- We reserve the right to make technical alterations without prior notice.	

Scope of delivery

Device	Quantity	Description
Junction boxes	1	Passive actuator/sensor junction box
PSGK-MC	2	Closure caps for M8 female connectors
KS5/10	9	Labels

Accessories

Ident-No.	Part Number	Description
U2-31580	RKC 10T-5/S3477	Connection cordset, female, M12, 10-pin, straight, 5m * (homerun)
UX10513	RKC 12T-5/S3477	Connection cordset, female, M12, 12-pin, straight, 5m * (homerun) (power pair)
U2-02854	BS 81121-0/PG9	Field-wireable, male, M12, 12-pin, straight,(6-8mm)
A1050	KS 5/10 (10/LABELS)	Labels
U0092-00	PSG 3-2	Cordset, male, Ø 8 mm (snap), 3-pin, straight, 2m * (I/O port)
U0138-2	PSW 3-2	Cordset, male, Ø 8 mm (snap), 3-pin, right-angle, 2m * (I/O port)
U2-11982	PSGK-MC (8/BAG)	Dust cap, male, Ø 8 mm (snap), (8/BAG)
A900154	TORQUE-WRENCH-SET-M12&M8-LEGACY	Torque wrench set, Torque driver, torque setting tool, M12 fitting, M8 fitting.
A900102	PICOBX ADAPTOR PLATE, 8 PORT (1PACK)	Allows new picobox to utilize the previous version mounting hole locations.

* Other lengths available on request